

Diablo Cable SRL

GUARDIAN
FALL PROTECTION

Part #	Length	Description
42009	33'	3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, & Steel Snap Hook
42010	33'	3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, Shock Pack, & Steel Snap Hook
42011	33'	3/16" Nylon Coated Galvanized Cable SRL w/Carabiner, Swivel Top, & Steel Snap Hook
42012	33'	3/16" Nylon Coated Galvanized Cable SRL w/Carabiner, Swivel Top, Shock Pack, & Steel Snap Hook
10968	50'	3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, Shock Pack, & Steel Snap Hook
10967	65'	3/16" Galvanized Cable SRL w/Carabiner, Swivel Top, Shock Pack, & Steel Snap Hook
10980	65'	3/16" Stainless Steel Cable SRL w/Carabiner, Swivel Top, Shock Pack, & Steel Snap Hook
10979	50'	3/16" Stainless Steel Cable SRL w/Carabiner, Swivel Top, Shock Pack, & Steel Snap Hook

Compliant with all OSHA 1910, OSHA 1926 Subpart M, ANSI Z359.14-2014, and ANSI A10.32-2012 regulations.

Repairable by the manufacturer. Contact customer service for details.

Diablo Cable SRL is suitable for the following applications:



Personal Fall Arrest: Diablo Cable SRLs may be used to support a MAXIMUM 1 Personal Fall Arrest System (PFAS) for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Applicable D-ring: Dorsal.

• **Free fall, Leading Edge (LE) Use:** Maximum 6'.

• **Free fall, non-LE Use:** Not permitted.



Restraint: Diablo Cable SRL may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.

**For all applications, worker weight capacity range (including all clothing, tools, and equipment):
130-310 lbs. for LE use, or 130-420 lbs. for non-LE use.**



WARNING Use of equipment in unintended applications may result in serious injury or death.

Materials: aluminum, galvanized steel, stainless steel, zinc-plated steel, high-strength ABS, and polyester.

Average arresting force: 1,350 lbs.

LE Use:

Min. setback distance from edge: 0'

Max. arresting distance: 54" - 102"

Min. fall clearance: 17' - 21'

Non-LE Use:

Max. arresting distance: 24"

Min. fall clearance: 6.5'

Class A SRL

MAXIMUM 1 user per Diablo Cable SRL. Dual Diablo SRL Kit is intended to facilitate 100% tie-off when transitioning between anchor points. During work, always attach unused SRL leg to compatible harness lanyard keeper.

Please contact Guardian Fall Protection for product-specific UPC-A Codes.

