

Specification Sheet 14311



DIMENSIONS:

Length (mm) Width - base (mm) Cord length (in)

28 mm 13 mm 28 inches

INFORMATION REQUIRED BY EPA:

The level of noise entering a person's ear, when a hearing protector is worn as directed, is closely approximated by the difference between the A-weighted environmental noise level and the NRR.

Example:

- 1. The environmental noise level as measured at the ear is 92 dBA.
- 2. The NRR is 33 decibels (dB).
- 3. The level of noise entering the ear is approximately equal to [92 dB (A) -33] 59 dB (A).

CAUTION: For noise environments dominated by frequencies below 500 Hz the C-weighted environmental noise level should be used. Improper fit of this device will reduce its effectiveness in attenuating noise. Consult the enclosed instructions for proper fit. Although hearing protectors can be recommended for protection against the harmful effects of impulsive noise, the Noise Reduction Rating (NRR) is based on the attenuation of continuous noise and may not be an accurate indicator of the protection attainable against impulsive noise such as gunfire.

PRODUCT DESCRIPTION:

DuraPlug[™] corded single use disposable foam earplug

- Super-soft, slow-recovery tapered shape foam for easy insertion and removal
- Low pressure, self-adjusting foam which offers long wearing comfort
- Noise Reduction Rating (NRR): 32 dB
- Compliance with ANSI S3. 19-1974
- Each pair individually wrapped

TECHNICAL DATA:

Material:	Polyurethane foam, poly cord	
Color:	Orange earplug, red cord	
Sizes:	One size only	
Packaging:	1 pair/polybag	
	100 polybags/box	
	10 boxes/case	
Registration Number (RN#):		78713
Country of Origin:		Taiwan
Harmonization Code (HTS#):		3926.90.9980

Liberty Glove & Safety | 433 Cheryl Lane, City of Industry, CA 91789 Phone: 1-800-327-8333 | Fax: 1-888-340-8333 | www.libertyglove.com | sales@libertyglove.com