

155-2-16 Specification Sheet

NOVAX RUBBER INSULATING GLOVES

PRODUCT DESCRIPTION:

Novax rubber electrical insulating gloves, class 2, 16-inch, black with orange liner.

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection.
- · Contoured shape reduces hand fatigue.
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability.
- · Silicone free.

Applications:

Used exclusively for electrical purposes, such as power generation, electrical contractors, hybrid automotive repair/service, hybrid automobile manufacturing, industrial plant maintenance, utilities.

TECHNICAL DATA:

Shell: Natural rubber Color: Black/Orange(155) Cuff Style: Straight, rolled Available Sizes: 8-11

Packaging: 1 pair per bag/box, 12 pair per case

Case Dimensions: (cm) - 55.3 x 22.1 x 9.7 / (in) - 21.8 x 8.7 x 3.8

Case Weight: 35.3 lbs / 16.0 kg

Manufacturer Certifications: ISO9001:2000 certified

 $\textbf{Country of Origin/Harmonization Code:} \ Malaysia/4015.19.1050$

MAX USE VOLTAGE:

AC V rms DC V
Class 2 17,000 25,500

NOVAX[™] by G.B. INDUSTRIES


ANSI / ASTM MADE IN D120
CLASS 2 MALAYSIA TYPE I
MAX USE VOLT 17000V AC

| BARCODE # | PAIR | CASE | |
|-------------|----------------|----------------|--|
| 155-2-16/8 | 01616314065650 | 02616314065659 | |
| 155-2-16/9 | 01616314065643 | 02616314065642 | |
| 155-2-16/10 | 01616314065667 | 02616314065666 | |
| 155-2-16/11 | 01616314065674 | 02616314065673 | |



DIMENSIONS:

| Size Available | <u>8</u> | <u>9</u> | <u>10</u> | <u>11</u> |
|----------------------|----------|----------|-----------|-----------|
| Over Length (cm) - A | 40.6 | 40.6 | 40.6 | 40.6 |
| (in) | 16.0 | 16.0 | 16.0 | 16.0 |
| Palm Width (cm) - B | 10.0 | 10.5 | 12.0 | 13.5 |
| (in) | 3.9 | 4.1 | 4.7 | 5.3 |
| | | | | |
| Max thickness (mm) | 2.29 | 2.29 | 2.29 | 2.29 |



This document is the property of PIP and the information contained herein is proprietary to PIP.