



# SPECIFICATION SHEET

## 162-2-18

### NOVAX® CLASS 2 RUBBER INSULATING GLOVES WITH CONTOUR CUFF – 18”

- Meet ANSI/ASTM D120 standard and NFPA 70E for use around electrical hazards and arc flash protection
- Contour cuff provides increased mobility and comfort
- Natural rubber construction offers the required dielectric properties combined with flexibility, strength and durability
- Silicone free

#### APPLICATIONS

- Power Generation
- Electrical Contractors
- Hybrid Automotive Repair/Service
- Hybrid Automobile Manufacturing
- Industrial Plant Maintenance
- Utilities

#### TECHNICAL DATA

|                 |   |
|-----------------|---|
| MATERIAL        | Natural Rubber                                |
| COLOR           | ■ Black / ■ Red                               |
| CUFF STYLE      | Contour, Rolled                               |
| SIZES           | 8 - 12  |
| PACKAGING       | 1 pair per box, 12 pair per case              |
| CASE DIMENSIONS | 21.8" x 8.7" x 3.8" / 55.3cm x 22.1cm x 9.7cm |
| CASE WEIGHT     | 35.3 lbs / 16.0 kg                            |
| COO             | Malaysia                                      |

#### MAX USE VOLTAGE

| CLASS | AC VOLTS | DC VOLTS |
|-------|----------|----------|
| 2     | 17,000   | 25,500   |



#### BARCODES

| ITEM          | BOX            | CASE           |
|---------------|----------------|----------------|
| ■ 162-2-18/8  | 01616314125737 | 02616314125735 |
| ■ 162-2-18/9  | 01616314125744 | 02616314125742 |
| ■ 162-2-18/10 | 01616314125706 | 02616314125704 |
| ■ 162-2-18/11 | 01616314125713 | 02616314125711 |
| ■ 162-2-18/12 | 01616314125720 | 02616314125728 |



#### DIMENSIONS (in/cm)

|          | 8         | 9          | 10        | 11         | 12        |
|----------|-----------|------------|-----------|------------|-----------|
| <b>A</b> | 18 / 45.7 | 18 / 45.7  | 18 / 45.7 | 18 / 45.7  | 18 / 45.7 |
| <b>B</b> | 3.9 / 10  | 4.1 / 10.5 | 4.7 / 12  | 5.3 / 13.5 | 5.9 / 15  |

Thickness: 3.5mm

