



Waterproof, Lightweight, Comfortable and Safe



Flite® is a Revolution in Protective Footwear.

Made from Aerex1.5.5® – a proprietary, chemical-resistant, thermally-insulative, microcellular polymer, resulting in boots that are over 40% lighter compared to most steel toe PVC and rubber knee boots. Superior chemical resistance to fats, oils, hydrocarbons, certain acids, and caustics makes Flite an excellent choice for food processing and petrochemical applications.

- Composite safety toe meets ASTM F2413 M/IC EH* and will not set-off metal detectors.
- Durable, seamless upper is 100% liquid proof.
- Slip-Resistant, nitrile rubber outsole provides superior grip on dry and wet-cleansurfaces.
- Tiny air bubbles trapped within the material keep feet warm in the cold and cooler in the heat.
- Aerex 1.5.5® is anti-fatigue since every pound reduced in footwear weight is like 5 pounds off your back and 5% less energy expended*.
- Calf-Relief Topline (CRT)™ is not only stylish, it provides easier on and off and roomier calf space
- Beveled heel for reduced back and leg strain.

Superior Comfort & Safety - Lightweight upper, cushioned heel, slip-resistant nitrile rubber outsole & ASTM composite toe.



Safety-Loc Outsole:

Maximum edges and ground contacting surfaces provide superior traction on wet, non-contaminated surfaces.

Ideal Applications: Wide Variety of Food Processing (Dairy, Meats, Vegetables, and Refrigerated/Frozen Foods), Chemical, and Petrochemical.

Chemical Resistance: Fats, oils, ketones, alcohols, hydrocarbons, acids, caustics, and other chemicals.



FLITE® SAFETY TOE KNEE BOOTS

■ 28259	Gray Upper - Orange Safety-Loc Outsole - Ht. 15" - Composite Toe	4 - 15
---------	--	--------

*Boot shall withstand 18,000 volts at 60 HZ for 1 minute with no current flow or leakage current in excess of 1.0 milliamperes under dry conditions tested as per lab conditions in Test Method F2412.

Electrical Hazard soles and heels are intended to reduce the hazards due to accidental contact with live electrical circuits, electrically energized conductors, parts, or apparatus. Electric Hazard soles and heels are not intended for wear in those work environments where volatile chemicals or explosives may be present, where conductive footwear is required.

Warning: Electric Hazard features of the soles and heels will deteriorate in wet environments, and when worn with excessive wear on the soles and heels.

#4063 - 9/18



ISO 9001 Certified

www.tingleyrubber.com

800•631•5498 fax 866•757•9239

