



**Supported Rough Finished Neoprene Chemical Handling Gloves** 

These 22-mil supported chemical handling gloves are constructed with black neoprene and lined with a seamless cotton liner. The grip of the palm and fingers is enhanced with a rough finish and the gloves are 15 inches in length.

### **INDUSTRY**

**Food Preparation** Chemical Handling

**Food Handling Material Handling** 

Laboratory Work Masonry

**Paper Manufacturing** Degreasing

Petrochemical **Battery Manufacturing** 

**Acids Handling** Cleaning

**Caustics Handling Food Processing** 

Food Service



- · Component materials comply with FDA regulations for food contact
- · Soft, cotton seamless liner is permanently adhered inside of the 22-mil black neoprene coating. This postprocess method ensures that the neoprene coating is a consistent thickness for the entire length of the glove
- The inserted liner provides extra comfort and durability compared to standard supported gloves
- including acids, caustics, oils and alcohols



## ITEM 245CT

- · Rough finish enhances grip in wet or greasy situations and provides extended wear
- · Waterproof
- · Not made with natural rubber latex
- 15 inches in length
- Straight cuff for extended forearm protection
- EN 388 Levels: 2132X

## SIZES ONE SIZE







### · Neoprene resists a wide range of chemicals, EN ISO 374-1:2016/Type A: AJKLMNOPT

# SPECIFICATIONS

LINER	COATING	COATING TYPE	COLOR	FINISH	LENGTH	THICKNESS
Cotton	Neoprene	Full	Black	Rough	15 in.	22-mil
CUFF	FDA FOOD CONTACT		EN 388 LEVELS		EN ISO 374-1:2016/TYPE A	
Straight	Compliant		2132X		AJKLMNOPT	

## **PACKAGING**

	QUANTITY	ONE SIZE
PAIR UPC	1	N/A
INNER PACK UPC	12/PACK	816368027449
CASE GTIN	6 PK/CASE	10816368027446
CASE WEIGHT (IN POUNDS)		42.9

13915 Radium St NW Ramsey, MN 55303

763-450-0110

Sales@GlobalGlove.com

GlobalGlove.com

## PFRMFATINN NATA

EN ISO 374-01: 2016	CHEMICAL	PL
A	Methanol	6
J	n-Heptane	3
K	Sodium Hydroxide 40%	6
L	Sulfuric Acid 96%	5
M	Nitric Acid 65%	6
N	Acetic Acid 99%	6
0	Ammonium Hydroxide 25%	6
Р	Hydrogen Peroxide 30%	6
T	Formaldehyde 37%	6

PERMEATION DATA WAS MEASURED IN TWO WAYS:

- 1. FOR SOLVENTS GAS CHROMATOGRAPHY
- 2. FOR ACID AND BASES -BY CONDUCTIVITY MEASUREMENTS



