

4" AC Power Recessed Downlight Kit

625 lm | 120VAC | Model 53182201 | Part DL-4-625-827-SV-D

- > Energy Saving 8 Watt Integrated LED
- > Uses 85% Less Energy than Equivalent 65 Watt Incandescent Bulb
- > Warm White 2700K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > IC Rated for Direct Contact with Insulation



SPECIFICATIONS

Model	53182201
Part	DL-4-625-827-SV-D
Description	4" AC Power Recessed Retrofit Downlight Kit
Input Voltage (VAC)	120
Wattage	8
Dimmability	Triac
Average Rated Life¹	50,000 hours
Typical Lumens²	625
CCT³	2700K
Location Rating	UL Wet
CRI⁴	80
Beam Angle	100
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	10
DUV	-0.0008
CBCP	289
Operating Frequency (Hz)	60

- 1 Hours lifetime with 70% lumen maintenance
 2 Thermally stable typical lumens (±10%)
 3 Thermally stable CCT (±10%)
 4 Color rendering index/Ra

ETi

LED lighting facts[®]
A Program of the U.S. DOE

Light Output (Lumens)	625
Watts	10
Lumens per Watt (Efficacy)	62.5
Color Accuracy	
Color Rendering Index (CRI)	80
Light Color	
Correlated Color Temperature (CCT)	2700 (Warm White)
2700K	3000K
4500K	6500K

All results are according to IESNA LM-79-2008. Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: YN84-4DBIBV (8/2/2017)
 Model Number: 531822##(##=01-11)
 Type: Retrofit Kit - Downlight

TO ORDER:
www.ETiSSL.com
 Call: 1.855.ETi.SSLI
 1.855.384.7754





4" AC Power Recessed Downlight Kit

625 lm | 120VAC | Model 53182201 | Part DL-4-625-827-SV-D

SHIPPING INFORMATION

Model	53182201
Part	DL-4-10-827-SV-D
UPC	849489006390
Product Dimensions (W x H in.)	4 7/8 x 1 5/8
Product Dimensions (W x H cm.)	12 1/2 x 4
Product Weight (lbs.)	0.25
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	4
Master Carton Bar Code	50849489006395
Master Carton Dimensions (L x W x H in.)	6.46 x 8.03 x 6.3
Master Carton Dimensions (L x W x H cm.)	16.4 x 20.4 x 16
Master Carton Weight (lbs)	2.03
Pallet Quantity	1008

COMPATIBILITY

Dimmers:

Lutron: CT-603PGH-WH, GL-600H-DK, MSCL-OP153M, MACL-153MH-WH, SCL-153PR-WH, TGCL-153PR-WH, TGCL-153PH-WH, TG-603PGH-WH, AYCL-153P-WH

Leviton: CD-C22-06672-12A, CD-R62-06674-12A, CD-R50-IPL06-12A, SB-011-IPL06-22A, 8100-I

Legrand: ADWR703HW4, ADPD453LM2

Cooper: DLC03PA-PTA, 9573A-PTA

Cans:

Commercial Electric: H9, H10, H13

Juno: IC1, IC91, IC1R

Halo: H99TAT, H99RTAT, H99ICAT

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256