



# 4' Linkable LED Strip Light

1800 lm | 120VAC | Model 54261143 | Part ST-4-20-840-SV-N

- > Energy Saving 20 Watt Integrated LED
- > Uses 87% Less Energy than Equivalent 32 Watt 1xT8 Fluorescent tube
- > Cool White 4000K CCT
- > Lasts 45 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > Suitable for use in closets, as defined in NEC® Section 410.16



## SPECIFICATIONS

|                                       |  |
|---------------------------------------|--|
| <b>Model</b>                          | 54261143                               |
| <b>Part</b>                           | ST-4-20-840-SV-N                       |
| <b>Description</b>                    | 4' Linkable LED Strip Light            |
| <b>Input Voltage (VAC)</b>            | 120                                    |
| <b>Wattage</b>                        | 20W                                    |
| <b>Dimmability</b>                    | Non-Dimmable                           |
| <b>Average Rated Life<sup>1</sup></b> | 50,000 hours                           |
| <b>Typical Lumens<sup>2</sup></b>     | 1800                                   |
| <b>CCT<sup>3</sup></b>                | 4000K                                  |
| <b>Location Rating</b>                | UL Damp                                |
| <b>CRI<sup>4</sup></b>                | ≥80                                    |
| <b>Beam Angle</b>                     | 107                                    |
| <b>Operating Temperature</b>          | Min -4°F (-20° C),<br>Max 95°F (35° C) |
| <b>Power Factor</b>                   | >0.9                                   |
| <b>R9</b>                             | 15                                     |
| <b>DUV</b>                            | -0.0002                                |
| <b>CBCP</b>                           | 296                                    |
| <b>Operating Frequency (Hz)</b>       | 60Hz                                   |

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754

**LED lighting facts**  
 A Program of the U.S. DOE

|   |                     |
|---|---------------------|
| Light Output (Lumens)                             | 1800                |
| Watts   | 20                  |
| Lumens per Watt (Efficacy)                        | 90                  |
| Color Accuracy<br>Color Rendering Index (CRI)     | 80                  |
| Light Color<br>Correlated Color Temperature (CCT) | 4000 (Bright White) |

2700K 3000K 4500K 6500K

Warm White Bright White Daylight

All results are according to IESNA LM-79-2008. Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: 58AM-ASF-DXA (9/22/2017)  
 Model Number: 54261143/ST-4-20-840-SV-N  
 Type: Luminaire - Linear





# 4' Linkable LED Strip Light

1800 lm | 120-277VAC | Model 54261143 | Part ST-4-20-840-SV-N

## SHIPPING INFORMATION

|  |                              |
|--|------------------------------|
| Model                                    | 54261143                     |
| Part                                     | ST-4-20-840-SV-N             |
| UPC                                      | 849489002590                 |
| Product Dimensions (L x W x H in.)       | 48 19/64 x 1 39/64 x 2 23/64 |
| Product Dimensions (L x W x H cm.)       | 122 x 4.1 x 6                |
| Product Weight (lbs.)                    | 3.45                         |
| Inner Carton Quantity                    | N/A                          |
| Inner Carton Bar Code                    | N/A                          |
| Inner Carton Dimensions (L x W x H in.)  | N/A                          |
| Inner Carton Dimensions (L x W x H cm.)  | N/A                          |
| Inner Carton Weight (lbs)                | N/A                          |
| Master Carton Quantity                   | 4                            |
| Master Carton Bar Code                   | 50849489002595               |
| Master Carton Dimensions (L x W x H in.) | 51.02 x 7.48 x 7.87          |
| Master Carton Dimensions (L x W x H cm.) | 129.6 x 19 x 20              |
| Master Carton Weight (lbs)               | 16.23                        |
| Pallet Quantity                          | 216                          |

## COMPATIBILITY

Dimmers: N/A  
Sensors: N/A

## AVAILABLE ACCESSORIES

| Model | Part | Description | Wattage | Input Voltage | Case Pack |
|-------|------|-------------|---------|---------------|-----------|
| N/A   | N/A  | N/A         | N/A     | N/A           | N/A       |

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etiled.us/fcc15b](http://www.etiled.us/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**ETi Solid State Lighting, Inc.**  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256