



2' Linkable LED Strip Light

900 lm | 120VAC | Model 54263143 | Part ST-2-10-840-SV-N

- > Energy Saving 10 Watt Integrated LED
- > Uses 87% Less Energy than Equivalent 20 Watt 1xT8 Fluorescent tube
- > Cool White 4000K CCT
- > Lasts 45 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty
- > Suitable for use in closets, as defined in NEC® Section 410.16



SPECIFICATIONS

Model	54263143
Part	ST-2-10-840-SV-N
Description	2' Linkable Strip Light
Input Voltage (VAC)	120
Wattage	10
Dimmability	Non-Dimmable
Average Rated Life¹	50,000 hours
Typical Lumens²	900
CCT³	4000K
Location Rating	UL Damp
CRI⁴	≥80
Beam Angle	107
Operating Temperature	Min -4°F (-20° C), Max 95°F (35° C)
Power Factor	>0.9
R9	15
DUV	-0.0002
CBCP	296
Operating Frequency (Hz)	60

1 Hours lifetime with 70% lumen maintenance
 2 Thermally stable typical lumens (±10%)
 3 Thermally stable CCT (±10%)
 4 Color rendering index/Ra

TO ORDER:
www.ETiSSL.com
 Call: 1.855.ETi.SSLI
 1.855.384.7754

ETI

LED lighting facts
A Program of the U.S. DOE

Light Output (Lumens)	900
Watts	10
Lumens per Watt (Efficacy)	90
Color Accuracy Color Rendering Index (CRI)	
80	
Light Color Correlated Color Temperature (CCT)	
4000 (Bright White)	
Warm White	Bright White
2700K	3000K
4500K	6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: 5BAM-R1C75V (9/22/2017)
 Model Number: 542631###(##=41-50)
 Type: Luminaire - Linear





2' Linkable Strip Light

900 lm | 120VAC | Model 54263143 | Part ST-2-10-840-SV-N

SHIPPING INFORMATION

Model	54263143
Part	ST-2-10-840-SV-N
UPC	849489002606
Product Dimensions (L x W x H in.)	24 x 4.0 x 2.0
Product Dimensions (L x W x H cm.)	61 x 10.16 x 5.1
Product Weight (lbs.)	1.81
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	6
Master Carton Bar Code	50849489002601
Master Carton Dimensions (L x W x H in.)	27.01 x 7.48 x 10.43
Master Carton Dimensions (L x W x H cm.)	68.6 x 19.0 x 26.5
Master Carton Weight (lbs)	11.68
Pallet Quantity	216

COMPATIBILITY

Dimmers: N/A
Sensors: N/A

AVAILABLE ACCESSORIES

Model	Part	Description	Wattage	Input Voltage	Case Pack
N/A	N/A	N/A	N/A	N/A	N/A

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256