

- > Energy Saving 10Watt Integrated LED
- > Uses 87% Less Energy than Equivalent 64Watt 2xT8 Fluorescent tube
- > Cool White 4000K CCT
- > Lasts 45 years or 50,000 **Hours Continuous Use**
- > Maintenance Free No **Bulb Replacements**
- > 5 Year Limited Warranty
- > Suitable for use in closets, as defined in NEC® Section 410.16 (C)

4' LED Strip Light

3600 lms | 120-277VAC | Model 54283144 | Part ST-4-40-840-MV-N

SPECIFICATIONS

54283144 Model

ST-4-40-840-MV-N Part 4' LED Strip Light Description

120-277 Input Voltage (VAC) 40W Wattage

Non-Dimmable Dimmability 50.000 hours Average Rated Life¹ 3600lm Typical Lumens²

4000K CCT³ **UL** Damp **Location Rating**

≥80 CRI⁴ 107 **Beam Angle**

Min -4°F (-20° C), **Operating Temperature**

Max 95°F (35° C)

Power Factor >0.9 15 R9 -0.0002DUV 296 **CBCP** Operating Frequency (Hz) 50/60Hz

- 1 Hours lifetime with 70% lumen maintenance
- 2 Thermally stable typical lumens (±10%) 3 Thermally stable CCT (±10%)
- 4 Color rendering index/Ra




TO ORDER:













4' LED Strip Light

3600 lms | 120VAC | Model 554283144 | Part ST-4-40-840-MV-N

SHIPPING INFORMATION

Model 54283144

Part ST-4-40-840-MV-N
UPC 849489002675
Product Dimensions (L x W x H in.) 48.02 x 2.2 x 3.9
Product Dimensions (L x W x H cm.) 122 x 56 x70

Product Weight (lbs.)

Inner Carton Quantity

N/A

Inner Carton Bar Code

N/A

Inner Carton Dimensions (L x W x H in.)

N/A

Inner Carton Dimensions (L x W x H cm.)

N/A

Inner Carton Weight (lbs)

N/A

Master Carton Quantity

1.81

N/A

N/A

Master Carton Bar Code 50849489002670

Master Carton Dimensions (L x W x H in.) 49.25 x 64.6 x 6.93

Master Carton Dimensions (L x W x H cm.) 125.1 x 16.4 x 17.6

Master Carton Weight (lbs) 15.46
Pallet Quantity 180

COMPATIBILITY

Dimmers: N/A Sensors: N/A

AVAILABLE ACCESSORIES

Model	Part	Description	Wattage	Input	Case
				Voltage	Pack
N/A	N/A	N/A	N/A	N/A	N/A

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.etiled.us/fcc15b

TO ORDER: www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754 ETi Solid State Lighting, Inc. 720 Corporate Woods Parkway Vernon Hills, IL 60061 Phone: 855.384.7754 Fax: 847.383.6256