

4' Linkable High Lumen Output Strip Light

5000 lm | 120-277VAC | Model 54573161 | Part ST-4-45-850-MV-D

- > Energy Saving 45 Watt Integrated LED
- > Daylight 5000K CCT
- > DLC Listed
- > Lasts 45 years or 50,000 Hours Continuous Use
- > 5 Year Limited Warranty
- > Suitable for use in closets, as defined in NEC[®] Section 410.16



SPECIFICATIONS

Model	54573161
Part	ST-4-45-850-MV-D
Description	4' Linkable High Lumen Output Strip Light
Input Voltage (VAC)	120-277
Wattage	45
Dimmability	0-10V Dimmable
Average Rated Life¹	50,000 hours
Typical Lumens²	5000
CCT³	5000K
Location Rating	UL Damp
CRI⁴	≥80
Beam Angle	100
Operating Temperature	Min -4°F (-20° C), Max 95°F (35° C)
Power Factor	>0.9
R9	18
DUV	0.0011
CBCP	1223
Operating Frequency (Hz)	50/60

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





4' Linkable High Lumen Output Strip Light

5000 lm | 120-277VAC | Model 54573161 | Part ST-4-45-850-MV-D

SHIPPING INFORMATION

Model	54573161
Part	ST-4-45-850-MV-D
UPC	849489002804
Product Dimensions (L x W x H in.)	48 x 1 13/16 x 2 13/64
Product Dimensions (L x W x H cm.)	122 x 4.6 x 5.59
Product Weight (lbs.)	3.2
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	6
Master Carton Bar Code	50849489002809
Master Carton Dimensions (L x W x H in.)	53.54 x 14.8 x 11.02
Master Carton Dimensions (L x W x H cm.)	136 x 37.6 x 28
Master Carton Weight (lbs)	22
Pallet Quantity	150

COMPATIBILITY

Sensors: 90600121

Dimmer Brand	Dimmer Model#
Lutron	DVTV-IV
Lutron	DVSTV-WH
Lutron	NFTV-WH
Lutron	NTSTV-DV-WH
Lutron	DVTV-WH
Leviton	IP710-DLZ

AVAILABLE ACCESSORIES

Model	Part	Description	Wattage	Input Voltage	Case Pack
95457326101	N/A	Aircraft Cable for Suspension Mounting (Two 10' pieces)	25	120-277	30
90600121	N/A	External Motion Sensor	N/A	120-277	4

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256