



40" Shop light

2800 lm | 120 VAC | Model 54590141 | Part SH-40-28-840-SV

- > Energy Saving 30 Watt Integrated LED
- > Cool White 4000K CCT
- > Lasts 45 years* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



SPECIFICATIONS

Model	54590141
Part	SH-40-28-840-SV
Description	40" Shop Light
Input Voltage (VAC)	120
Wattage	30
Dimmability	NA
Average Rated Life ¹	50,000 hours
Typical Lumens ²	2800
CCT ³	4000K
Location Rating	UL Damp
CRI ⁴	80
Beam Angle	NA
Operating Temperature	Min -4°F (-20° C), Max 113°F (45° C)
Power Factor	>0.9
R9	15
DUV	-0.00194
CBCP	NA
Operating Frequency (Hz)	60

¹ Hours lifetime with 70% lumen maintenance

² Thermally stable typical lumens (±10%)

³ Thermally stable CCT (±10%)

⁴ Color rendering index/Ra

TO ORDER:

www.ETiSSL.com

Call: 1.855.ETi.SSLI

1.855.384.7754





40" Shop light

2800 lm | 120 VAC | Model 54590141 | Part SH-40-28-840-SV

SHIPPING INFORMATION

Model	54590141
Part	SH-40-28-840-SV
UPC	849489002132
Product Dimensions (L x W x H in.)	40 x 3.14 x 2.05
Product Dimensions (L x W x H cm.)	101.6 x 8 x 5.2
Product Weight (lbs.)	2.52
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	6
Master Carton Bar Code	50849489002137
Master Carton Dimensions (L x W x H in.)	47.32 x 10.55 x 9.06
Master Carton Dimensions (L x W x H cm.)	120.2 x 26.8 x 26.6
Master Carton Weight (lbs)	22.34
Pallet Quantity	TBD

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETiSSL.com/fcc15b

TO ORDER:
www.ETiSSL.com
Call: 1.855.ETi.SSLI
1.855.384.7754

ETi Solid State Lighting, Inc.
720 Corporate Woods Parkway
Vernon Hills, IL 60061
Phone: 855.384.7754
Fax: 847.383.6256