



# HAND PROTECTION

## Lightweight, Seamless, New Foam Technology Palm Coated, rPET Recycled Gloves with Cut, Abrasion, and Puncture Resistance

### DESCRIPTION

These general-purpose gloves have a 15-gauge gray-and-black seamless rPET/nylon/spandex shell. Recycled polyester (rPET) fiber utilizes reprocessed PET plastic bottles as an environmentally conscious method to help reduce carbon dioxide emissions. The palm is coated with black New Foam Technology nitrile, providing excellent dexterity and grip. Features touch screen compatible fingertips and a knit wrist cuff for a secure fit. ANSI/ESD anti-static/electrostatic compliant for use in an ESD-protected area.



INDUSTRY		
Agriculture	Maintenance	Handling
Assembly	General Purpose	Painting
Automotive	Landscaping	Small Parts Handling
Construction	Manufacturing	Warehousing
General	Material	

### FEATURES

- 15-gauge rPET/nylon/spandex shell offers bare hand sensitivity
- Nitrile-coated palm with New Foam Technology finish allows hands to breathe while providing great grip in wet, oily, or dry conditions
- Made with rPET (recycled polyester) fiber which utilizes reprocessed PET plastic bottles as an environmentally conscious method to help reduce carbon dioxide emissions. This process helps to reduce 227 grams of carbon dioxide emission, 0.387 kWh of electricity, and over 1 gallon of water per pair
- Overcast color on hem for easy size identification
- Touch screen compatible fingertips
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use

### SPECIFICATIONS

SHELL	SHELL COLOR	GAUGE	COATING	COATING COLOR	COATING TYPE	FINISH	CUFF	TOUCH SCREEN	ANSI CUT
rPET/Nylon/Spandex	Gray and Black	15-Gauge	Nitrile	Black	Palm	New Foam Technology	Knit Wrist	Yes	Level A1
ASTM F2992-15 RESULTS	ANSI ABRASION	ANSI PUNCTURE	PUNCTURE RESULTS	ANSI/ESD ANTI-STATIC/ELECTROSTATIC	EN 388 LEVELS	EN 407 LEVELS			
330 Grams	Level 3	Level 2	42 Newtons	Compliant	4131A	X1XXXX			

### PACKAGING

	QUANTITY	6(XS)	7(S)	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	NA	NA	NA	NA	NA	NA
INNER PACK UPC	12/PACK	810033293306	810033294785	810033294792	810033294808	810033294815	810033294822
CASE GTIN	6 PK/CASE	10810033293303	10810033294782	10810033294799	10810033294805	10810033294812	10810033294829
CASE WEIGHT (IN POUNDS)		6.49	7.5	8.5	9.5	9.9	10.25
OVERCAST COLOR		Purple	Red	Green	Brown	Black	Light Blue

### ITEM 600NFT SIZES 6(XS)-11(2XL)

- ANSI/ISEA 105 Cut Level A1
- ASTM F2992-15 Results = 330 grams
- ANSI/ISEA 105 Abrasion Level 3
- ANSI/ISEA 105 Puncture Level 2
- ANSI/ISEA 105 Puncture Results: 42 Newtons
- ANSI/ESD anti-static/electrostatic compliant
- EN 388 Levels: 4131A
- EN 407 Levels: X1XXXX



13915 Radium St NW  
Ramsey, MN 55303

763-450-0110  
Sales@GlobalGlove.com

GlobalGlove.com

  
**Global Glove**  
& Safety Manufacturing, Inc.