



Lightweight upper, cushioned heel, slip-resistant nitrile rubber outsole and ASTM composite toe.



Cleated Outsole: Spits out debris for grip on indoor and outdoor surfaces.

FLITE® SAFETY TOE WORK SHOE

■ ■ 27211	Black Upper – Black Cleated Outsole - Ht. 6" – Composite Safety Toe – EH Rated	4 – 15
-----------	--	--------

Ideal Applications: Warehouses, Work Shops, Construction, Transportation, Municipalities, Janitorial, and a wide array of Food Processing (Dairy, Meats, Vegetables, and Breweries).

Chemical Resistance: Superior chemical resistance to fats, oils, hydrocarbons, and many acids and alkalis.

FLITE® CST Work Shoe is a Revolution in Protective Footwear

Superior comfort, ASTM F2413 compliant toe cap and EH rating, 100% waterproof, and outstanding slip resistance make the Flite Work Shoe an excellent choice for warehouse and distribution center workers, municipalities, transportation crews and a wide array of food processing applications.

- Lightweight Aerex 1.5.5® construction provides unbeatable all-day comfort.
- Composite safety toe meets ASTM F2413 M/IC EH* and will not set-off metal detectors.
- 100% liquidproof, and chemical resistant to a wide range of chemicals, acids, alkalis and oils.
- Slip-Resistant, nitrile rubber outsole provides superior grip on dry and wet, clean and contaminated surfaces.
- Tiny air bubbles trapped within the material are self-insulating to keep feet warm in the cold and cooler in the heat.
- Unique thumb pocket at the top opening allows firm, no-slip grip for easy donning.
- Wrap around heel kick for hands-free removal.
- No shoelaces to contaminate or cause a trip-and-fall hazard.
- Removable, contoured insole absorbs energy of heel strikes which alleviates impacts to the foot while walking to minimize risk of injuries.



WATERPROOF



LIGHTWEIGHT



INSULATING



SAFETY TOE



CHEMICAL RESISTANT



OIL RESISTANT



SLIP RESISTANT



ELECTRICAL HAZARD

*Boot shall withstand 18,000 volts at 60 HZ for 1 minute with no current flow or leakage current in excess of 1.0 milliamperes under dry conditions tested as per lab conditions in Test Method F2412.

Electrical Hazard soles and heels are intended to reduce the hazards due to accidental contact with live electrical circuits, electrically energized conductors, parts, or apparatus. Electric Hazard soles and heels are not intended for wear in those work environments where volatile chemicals or explosives may be present, where conductive footwear is required.



#4058 – 6/20