



# SPECIFICATION SHEET

9100-52422



## 40 CAL/CM<sup>2</sup> - FLAME RESISTANT OVERALLS

- ARC Rating: ATPV 40 cal/cm<sup>2</sup>
- PPE 4 (HRC 4)
- Aramid high tenacity thread
- Bar-tacked at all stress points
- No metal pieces on garment
- Hook and loop adjustment at sides and bottom ankle cuffs
- Pass through pockets
- Covered zipper fly closure
- Elasticized waist

## STANDARDS MET

- NFPA 70E-2012
- ASTM F1506-10a
- ASTM F2178-12
- OSHA 29 CFR 1910.269

## APPLICATIONS

- Electrical & Utilities

## CARE INSTRUCTIONS

Machine wash warm, 165° F max. Tumble dry low. DO NOT bleach. DO NOT use fabric softener. DO NOT iron.

## TECHNICAL DATA

MATERIAL	Westex Ultrasoft 88% Cotton 12% High Tenacity Nylon
CONSTRUCTION	Two Layers; 9 oz FR Cotton over 13 oz FR Cotton
COLOR	■ Navy
SIZES	S - 5X
PACKAGING	1/polybag
CASE SIZE	12" x 12" x 6" / 30.5cm x 30.5cm x 15.25cm
CASE WEIGHT	4 lbs / 1.8 kg
COO	USA

## BARCODES

ITEM	BAG	BOX	CASE
■ 9100-52422/S	616314136290	01616314136299	02616314136298
■ 9100-52422/M	616314136283	01616314136282	02616314136281
■ 9100-52422/L	616314136276	01616314136275	02616314136274
■ 9100-52422/XL	616314136306	01616314136305	02616314136304
■ 9100-52422/2X	616314136238	01616314136237	02616314136236
■ 9100-52422/3X	616314136245	01616314136244	02616314136243
■ 9100-52422/4X	616314136252	01616314136251	02616314136250
■ 9100-52422/5X	616314136269	01616314136268	02616314136267



## DIMENSIONS (in)

	M	L	XL	2X
<b>A</b>	36-38	40-42	44-46	48-50
<b>B</b>	32	32	32	32

