



SPECIFICATION SHEET

9150-52689



100 CAL/CM² ARC HOOD

- Arc Rating: ATPV 100 cal/cm²
- PPE 4 (HRC 4)
- Incorporates UV and IR-absorbing ARC shield lens providing protection up to 100 cal/cm²; replaceable
- Green tint window is coated with a permanent anti-fog inner surface
- Lens is extended 3" from face to accommodate respiratory protection and help minimize lens fogging
- Lens meets ANSI Z87.1
- Supplied with dielectric safety helmet and hard hat adapter

STANDARDS MET

- NFPA 70E 2012
- ASTM F1506-2010a
- OSHA 29 CFR1910.269

APPLICATIONS

- Electrical & Utilities
- Petrochemical, Gas & Oil
- Mining
- Welding
- Emergency Services

CARE INSTRUCTIONS

Hood: Machine wash warm, 165°F max. Tumble dry low. DO NOT bleach. DO NOT use fabric softener. DO NOT iron.

Lens: Clean and inspect before and after use. Clean with a damp cloth unless heavily soiled. Should further cleaning be required, clean with mild soap and water, pat dry. Disassemble if required, for cleaning and inspection.

TECHNICAL DATA

MATERIAL	Westex Ultrasoft 88% Cotton 12% High Tenacity Nylon
CONSTRUCTION	Multi-Layer: 2 layers of 13 oz FR Cotton over 2 layers of 5.5 oz FR Cotton
COLOR	■ Taupe Grey
SIZES	OSFM
PACKAGING	1/bag
CASE SIZE	16" x 16" x 12" / 40.6cm x 40.6cm x 30.5cm
CASE WEIGHT	5 lbs / 2.3 kg
COO	USA

BARCODES

ITEM	BAG	BOX	CASE
■ 9150-52689	616314137594	01616314137593	02616314137592



DIMENSIONS (in)

	OSFM					
A	32					

