

20-Gallon OverPack Salvage Drum #A20OVER - 23" dia x 19.5", 1 each/package



Stock a SpillTech® OverPack with sorbents for emergency spill response, or use it as a salvage drum to ship damaged containers or hazardous waste.

- Tough UN Rated overpack is built to withstand rough handling. Guaranteed.
- X-rated for Packing Groups I, II and III, so it's ideal for regulated packaging applications, including shipping hazardous waste by land, sea or rail
- Polypropylene material with UV inhibitors is durable, lightweight and chemical-resistant
- Containers are nestable when empty to save storage space
- Designed and proven to withstand the abuse of shipping to help keep hazardous waste safely contained
- Specifically designed and sized for leaking cans, bottles or 5gallon pails
- Leakproof, twist-on lid is notched so you can easily tighten it with a 2x4 or pole
- Integrated ledges and handles molded into container let you move overpack with a forklift or by hand

A200VER Specifications

Dimensions: ext. dia. 23" x 19.5" H **Shipping** 23" W x 23" L x 19.5" H

Dimensions:

Sold as: 1 per package

Color: Yellow

Composition: Copolymer-polypropylene

Weight: 11.9 lbs. **# per Pallet:** 40

Incinerable: No

UN RATING: 1H2/X66/S

Ship Class: 250

Metric Equivalent Specifications

Dimensions: ext. dia. 58.4cm x 49.5cm H

Shipping 58.4cm W x 58.4cm L x 49.5cm H

Dimensions:

Weight: 5.4 kg



Online: spilltech.com

ine: Phone: :h.com 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com

A200VER Technical Information

Warnings & Restrictions:

There are no known warnings and restrictions for this product.

Regulations and Compliance:

49 CFR 173.3(c)(1) - If a container of hazardous waste is damaged or leaking, it can be placed in a compatible salvage drum that meets UN criteria for shipping

49 CFR 173.12(b)(2)(iv) - When labpacking, "Inner packagings...must be surrounded by a chemically compatible absorbent material in sufficient quantity to absorb the total liquid contents."

49 CFR 173.12(b) - A container used for labpacking must be "a UN 1A2 or UN 1B2 metal drum, a UN 1D plywood drum, a UN 1G fiber drum or a UN 1H2 plastic drum tested and marked at least for the Packing Group III performance level for liquids or solids."

Technical Documents:

(Available at **spilltech.com**)
Product Data Sheet (PDS)

Chemical Compatibility (CCG)



Phone: 1-800-228-3877 (N.Am.) 1-770-475-3877 (Other) Fax: 1-800-872-3764 (N.Am.) 1-770-410-1812 (Other) Email: sales@spilltech.com