

Latex Industrial Gloves




Features and Benefits

- Elastic and highly flexible for exceptional comfort and dexterity.
- Cream Color.
- Powder Free.
- Single Use Only.
- Textured surface for improved grip.
- Complies with FFDCa food handling requirements 21 CFR, Parts 170-199.

Specifications



Usage



Ordering Information

ITEM NUMBER	SIZE	FINGER THICKNESS	PALM THICKNESS	GRAM WEIGHT*	INNER BOX	OUTER CASE
A33A11	SM	5.0 mil +/- 0.5 mil	4.0 mil +/- 0.5 mil	5.0g +/- 0.2g	8-10052-97100-1	008-10052-97101-8
A33A12	MD				8-10052-97103-2	008-10052-97104-9
A33A13	LG				8-10052-97106-3	008-10052-97107-0
A33A14	XL				8-10052-97109-4	008-10052-97110-0

*Based on size M

ITEM NUMBER	QUANTITY	INNER BOX DIMENSIONS	CASE DIMENSIONS	TI/HI	CASE WEIGHT (LBS.)	COUNTRY OF ORIGIN
A33A11	100/bx 10 bx/cs	8.7 x 4.5 x 2.6"	13.8 x 9.3 x 8.9"	15/7	12	Indonesia Malaysia
A33A12					14	
A33A13					14	
A33A14					15	

Finding the right hand protection doesn't have to be complicated. Consider VGuard® gloves as an extension of our promise to you: High quality products, great value and excellence in service. If ever you have a question regarding which glove is best for your application, we're here to help. VGuard® is protection you can count on!

Vanguard Safety

Cumming, GA 30041 • 1-866-VGUARD-6 (1-866-848-2736)
 Info@VanguardSafety.com • www.VanguardSafety.com

Latex Industrial Gloves



Composition

Material:	Natural Rubber Latex
Allergen content:	Less than 200 µg/dm ² as per ASTM D5712
Powdered:	No, as per ASTM D6124

Quality

Quality Assurance:	ISO:9001
Regulatory Compliance:	Complies with FFDCa food handling requirements 21 CFR, Parts 170-199

Technical Data

THICKNESS	MIL
Palm:	4.0 ± 0.5
Finger:	5.0 ± 0.5

Weight*:	5.0 gm ± 0.2
-----------------	--------------

*Based on size M

PHYSICAL PROPERTIES	BEFORE AGING	AFTER AGING
Tensile Strength (MPa):	Min. 14	Min. 14
Ultimate Elongation (%):	Min. 650	Min. 500
Freedom from holes:	AQL 4.0	N/A

DIMENSIONS			
ITEM NO.	SIZE	PALM WIDTH (mm)	LENGTH (mm)
A33A11	Small	80 ± 10	Min. 220
A33A12	Medium	95 ± 10	Min. 230
A33A13	Large	110 ± 10	Min. 230
A33A14	XL	120 ± 10	Min. 230

COUNTRY OF ORIGIN	HARMONIZATION CODE
Indonesia & Malaysia	4015.19.1110

Vanguard Safety

Cumming, GA 30041 • 1-866-VGUARD-6 (1-866-848-2736)
 Info@VanguardSafety.com • www.VanguardSafety.com