# **LITETRONICS®**

# LED AREA LIGHT PRO

ONE AREA LIGHT. EVERY APPLICATION.

#### DESCRIPTION

Litetronics patented Area Light Pro Series is designed to simplify outdoor lighting installations. Featuring field-selectable wattages, color temperatures, and optical distributions, a single fixture can replace dozens of SKUs, streamlining inventory and planning. Quick Slide mounting system allows for effortless installation. Simply slide the fixture into the mount, saving time and resources on every job. Equipped with a universal 120-480V driver, 20kV surge protection, and plug-and-play smart controls, it's built for reliability, ease of use, and lower total cost of ownership. Perfect for all outdoor lighting needs including: parking lots, campuses, industrial yards, and retail spaces, the Area Light Pro offers powerful performance with unmatched flexibility.

#### **FEATURES & ACCESSORIES**

- All-in-one 120-480V
- DLC 5.1 Premium (Pending)
- Type II, III, IV, V Selectable Distribution
- Field Selectable Wattages & CCT
- 10-Year Warranty
- 100,000-Hour Rated Life
- 3-pin Shorting Cap (Standard) Smart Node Ready with Nema 7 Pin Receptacle (Optional)
- TAA Compliant

**Order Code** 

ALP150

ALP250

ALP500

Pluggable Sensor Socket

Length

16.3"

17.9"

**DIMENSIONS / WEIGHT** 

- Compatibility with LiteSmart
- Optional Glare Shields to Meet Code and Local
- Optional Slipfitter, Pole Tenon, and Trunnion Mountings Available
- Optional 3-Pin Photo

#### Quick Slide Mounting

- Mobile App
- Ordinance
- Control
- Patented Area Light Pro Design

Height

2.4"

2.4"

2.4"

Height

Weight

8.5 lbs.

9 lbs.

14.6 lbs.

# PROJECT:



#### **MARKETS**

- Car Dealership
- Schools, Campuses, Day Care
- Parking Lots
- Commercial


- Transportation Hubs
- Trucking Depots
- Retail
- Event Centers
- Industrial Yards and Lots

### **MOUNTING**

- Slipfitter
- Trunnion

- Round/Square Pole Tenon
- Wall or Pole Mount

#### 14.2" 26.8"



Width

11"

16.3"

## **CERTIFICATIONS**









#### **SPECIFICATIONS**

Life (@L70): 100,000 hours Warranty: 10 years

#### **PERFORMANCE**

**Operating temp:** -40F to  $122^{\circ}F$  ( $-40^{\circ}C$  to  $50^{\circ}C$ )

Efficacy (LPW): 160

**CRI:** >80

#### **ELECTRICAL**

Input voltage: 120-480V Input frequency: 50/60Hz

**PF:** ≥0.9 **THD:** < 20%

Surge protection: 20KV

**Dimming:** 0-10V **Whip/Cord:** 1.6′

**Sensor:** Plug-In Occupancy Motion Sensor (Choice of Microwave, PIR, Bluetooth)

#### **OPTICAL**

Beam: Type II, III, IV, V Selectable

Lens: Polycarbonate

UGR: N/A

#### **PHYSICAL**

Finish: Matte Powder Coat
Color: Dark Bronze/Black/White
Housing: Die-Cast Aluminum

#### **INDUSTRY STANDARDS/RATINGS**

**Bug Rating:** B4-U0-G4

IP: 65 IK: 08

Location: Wet
Outdoor Rated: Yes
UL/ETL: ETL (Pending)

FCC: Yes RoHS: Yes

**DLC:** 5.1 Premium (Pending)

TAA: Compliant

#### **MOUNTING**

Optional: Slipfitter, Trunnion, Tenon, and Wall/Pole mounting available

#### **QUICK-SLIDE MOUNTING**

The Roadway Pro features our Quick-Slide attachment, designed to make mounting faster and more flexible than ever. With two screws, you can easily slide, reposition, or swap mounting methods, giving you the freedom to install the fixture exactly how the job requires.





#### **ORDERING INFORMATION**

#### Main Fixture

Ordering Code	Description	Watts	Volts	CCT (K)	Lumens
ALP150	Area Light Pro 150W - Dark Bronz	100   125   150	120-480V	3000   4000   5000	16000   20000   24000
ALP250	Area Light Pro 250W - Dark Bronz	175   200   250	120-480V	3000   4000   5000	28000   32000   40000
ALP500	Area Light Pro 500W - Dark Bronz	300   400   500	120-480V	3000   4000   5000	48000   64000   80000

Note: Color options can be found on the color matrix on page 3.

#### **ACCESSORIES**

#### **Accessories - Sensors & Controls**

Ordering Code	Image	Description	Usage
OLAPC		3-pin photocontrol, 120-480v	Enables fixture to turn on/off based on daylight levels
SC005		Plug-in PIR Sensor	Enable occupancy sensing and daylight harvesting on pluggable fixtures.
SC006		Plug-in Microwave Sensor	Enable occupancy sensing and daylight harvesting on pluggable fixtures.
SC011		Bluetooth PIR Sensor with IR	This sensor enables wireless control of fixtures, or groups of fixtures, through the LiteSmart mobile app
SCR053		Remote Control for plug-in PIR and Microwave sensors	Used to adjust sensor settings after installation, from the ground. (For SC005 & SC006)
SCR054	= = 9	Remote Control for bluetooth plug-in PIR and Microwave sensors	Used to Commission LiteTronics "Next Generation" LiteSmart IR-Enabled Sensor. (For SC0011)



#### **Accessories - Mounts**

Ordering Code	Image	Description	Usage		
ALPASFM*	Slipfitter Mount		Area Light Slip Fitter Quick Slide Mount - Dark Bronze		
ALPAPM*		Round-Square Pole Tenon & Slipfitter Mount	Area Light combination Tennon & Quick Slide Slipfitter mounts for round/square poles - Dark Bronze		
ALPATM*	Trunnion Mount		Area Light Trunnion Quick Slide Mount - Dark Bronze		
ALPAADM*		Adjustable Direct Wall or Pole Mount	Area Light Pro Quick Slide Adjustable Direct Wall or Pole Mount - Dark Bronze		

Note: Color options can be found on the color matrix on page 3.

#### **Accessories - Glare Shields**

Ordering Code	Image	Description	Usage
ALPAGS1S	P. MICHAELINI	Area Light Pro Glare Shield - Side	Area Light Pro Glare Shield for 150 watts - Side (right or left, 2 parts required for both)
ALPAGS1C		Area Light Pro Glare Shield - Center	Area Light Pro Glare Shield for 150 watts - Center (front or back, 2 parts required for both)
ALPAGS2S	- 1 mumum	Area Light Pro Glare Shield - Side	Area Light Pro Glare Shield for 250 watts - Side (right or left, 2 parts required for both)
ALPAGS2C		Area Light Pro Glare Shield - Center	Area Light Pro Glare Shield for 250 watts - Center (front or back, 2 parts required for both)
ALPAGS5S		Area Light Pro Glare Shield - Side	Area Light Glare Pro Shield for 500 watts - Side (right or left, 2 parts required for both)
ALPAGS5C		Area Light Pro Glare Shield - Center	Area Light Glare Pro Shield for 500 watts - Center (front or back, 2 parts required for both)

Note: Color options can be found on the color matrix below.

#### **Glare Shield IES Refrence Guide**

The diagram below identifies fixture orientations to assist in selecting the correct IES file for glare shield configurations. Separate IES files are provided based on which side(s) or position(s) the glare shield is installed.

Street Side
Front
(Center)

Left
(Side)

House Side
Back

(Center)

## Color Matrix

Name	Dark Bronze	Black	White			
Main Fixture						
Area Light Pro - 150W	ALP150	ALP150B*	ALP150W*			
Area Light Pro - 250W	ALP250	ALP250B*	ALP250W*			
Area Light Pro - 500W	ALP500	ALP500B*	ALP500W*			
Mounts						
Slipfitter Mount	ALPASFM	ALPABSFM*	ALPAWSFM*			
Tenon Mount	ALPAPM	ALPABPM*	ALPAWPM*			
Trunnion Mount	ALPATM	ALPABTM*	ALPAWTM*			
Wall or Pole Mount	ALPAADM	ALPABADM*	ALPAWADM*			
Glare Shields						
Glare Shield - Side (150W)	ALPAGS1S*	ALPABGS1S*	ALPAWGS1S*			
Glare Shield - Center (150W)	ALPAGS1C*	ALPABGS1C*	ALPAWGS1C*			
Glare Shield - Side (250W)	ALPAGS2S*	ALPABGS2S*	ALPAWGS2S*			
Glare Shield - Center (250W)	ALPAGS2C*	ALPABGS2C*	ALPAWGS2C*			
Glare Shield - Side (500W)	ALPAGS5S*	ALPABGS5S*	ALPAWGS5S*			
Glare Shield - Center (500W)	ALPAGS5C*	ALPABGS5C*	ALPAWGS5C*			

<sup>\*</sup> Note: Made to order only.



#### FIXTURE POLE CONFIGURATION AND EPA WIND RATING

From single to double to quad configurations, Litetronics Area Lights Pro can accommodate the needed number of fixtures per pole to meet all application needs.

Product	Fixture Position	•	<b>!_</b>			人	
		Single Fixture	2 Fixtures at 90°	2 Fixtures at 180°	3 Fixtures at 90°	3 Fixtures at 120°	4 Fixtures at 90°
150W	Horizontal	0.325	0.507	0.654	0.772	0.833	0.772
	45°	1.494	2.032	1.494	2.585	3.618	2.585
250W	Horizontal	0.359	0.560	0.722	0.852	0.921	0.852
	45°	1.853	2.520	1.853	3.206	4.488	3.206
500W	Horizontal	0.529	0.825	1.065	1.256	1.357	1.256
	45°	3.205	4.359	3.205	5.545	7.763	5.545

Note: Litetronics does not manufacture or sell poles.

#### WIRELESS CONTROL WITH PLUGGABLE SENSORS



The optional Microwave (SC006), and PIR Sensor (SC005) use a remote control for easy setup and control of individual fixtures.



The smart PIR sensor uses a remote control (SCR054) to Commission and group Litetronics "Next Generation" LiteSmart IR-Enabled SC011 Sensor.



# LITESMART





LiteSmart is a mobile app that enables total management of lighting systems at the touch of your fingers. Within the app, all functionality can be set up and controlled; on/off, dimming, grouping, scene creation and time scheduling. Adjustments can also be made to the occupancy sensor settings, then implemented across an entire group in seconds.

- Total control over your lighting system
- Quick and easy changes that can be implemented in seconds across a group of fixtures
- Further energy reduction via occupancy sensing, and max wattage control
- Ability to create custom scenes based on specific needs, such as presentations
- Time scheduling that sets hours of operation per day



Set up and manage your space with LiteSmart.

**Disclaimer:** Specifications are subject to change without notice. While Litetronics makes every effort to ensure accuracy, we do not guarantee the completeness or reliability of the information provided. For the most current product data, please visit www.litetronics.com.

