	ration Date 3.11 on-belted FBH Lock-	
n:	on-belted FBH Lock	-QC
lowing performand	-	with
59.11-2014		
	NSI/ISEA 125-2014	
the Scope of	Level 3: Independent 3rd F accredited to ISO/IEC Standard 17025	-
	lowing performanc 59.11-2014	n accordance with ANSI/ISEA 125-2014       I 2     X       Level 3       FallTech Lab       the Scope of

Exova 3883 East Eagle Drive Anaheim California USA 92807 T: +1 (714) 630-3003 F: +1 (714) 630-4443 E: sales@exova.com W: www.exova.com



Testing. Advising. Assuring.

April 21, 2016

FallTech Testing Laboratory 1306 S. Alameda Street Compton, CA 90221

Attention: Jay Sponholz Quality Manager

Subject:

Attestation of Witnessing TestingExova OCM Job #360527-5FallTech P.O.:OPENReport No.:PC-0801Base Part No.7087BQSDescription:Full Body Harness

Dear Mr. Sponholz:

The purpose of this attestation is to attest to the fact that a representative of Exova OCM was on site at FallTech's facilities to confirm suitability of the equipment used, calibration status of the equipment and to witness testing performed by FallTech employees. Details of this visit are included below:

- Date of Testing:
  - 10 March 2016
- Exova OCM Test Witness:
  - Robert Fortner
- FallTech Test Operators:
  - Yesbet Sierra and Jay Sponholz
- Specification:
  - ANSI Z359.11-2014 Sections 4.3.3, 4.3.5, 4.3.6, 4.3.7
- Equipment Calibration Interval
  - 1 year, except weights which are 5 years



Attached to this attestation is the test report generated by FallTech Testing Laboratory. Exova OCM test witness certifies the report accurately presents the testing performed on the samples identified.

Test Report #	Date	Base Part #	Description	Sample ID's	Results
		0		3133961	
				3133968	
				3133962	
		7087BQS Full Body Harness	7087BQS Full Body Harness	3133963	
PC-0801	3/11/2016			2	Pass
				3133965	
				3133960	
				3133966	
			3133967		

Test Witness Signature:	(Signed for and on behalf of Exova-OCM)	$\sim$
Robert Fortner Technician Mechanical Laboratory	Robert Forten	Len Jan

Approval Signature:	(Signed for and on behalf of Exova-OCM)	OCA
Thomas J. (Tom) Parsons Manager Quality / Technical Services	Jan Darsman	(3054 (1995)

This attestation shall not be reproduced except in full, without the written approval of Exova-OCM. The laboratory has witnessed the testing the material / items supplied by the client as sampled by the client. The testing is not within Exova OCM's L.A.B scope of testing and was not performed at Exova OCM.



FallTech Testing Laboratory Attestation Number: 360527-5 Revision Letter: Original Page 2 of 2



3133960

3133966

3133967

# **FallTech Testing Laboratory**

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

FallTech Test Report							
Test Report Number	PC-0801	Date	3/11/2016	Rev	1	Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden Test Specification			ANSI Z359. 4.3.5, 4.3.3,	11-2014 4.3.6, 4.3.7		
Base Part #	7087BQS	7087BQS Description			arness		
Proposed Part #	N/A	Built By Whom		Production		BOM	No
Test Request #	PC-0801	Date Recei	ved	1/15/2016	Date C	Complete	3/10/2016
Test Operator	Jay Sponholz	Test Opera	tor	Yesbet Sierra			
	M	laterial/San	nple Identificati	on			
Sample ID			Descrip	tion			
3133961			Full Body H	larness			
3133968		Full Body Harness					
3133962		Full Body Harness					
3133963			Full Body H	larness			
2			Full Body H	larness			
3133965			Full Body H	larness			

Full Body Harness

Full Body Harness

Full Body Harness







FallTech Test Report							
Test Report Number	PC-0801	Date	3/11/2016	Rev		Rev Date	
Report Prepared For FallTech							
Initiated By	Dan Redden	Tast Specification		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.6, 4.3.7			
Base Part #	7087BQS	Description	า	Full Body Harness			
Proposed Part #	N/A	Built By Whom		Production		BOM	No
Test Request #	PC-0801	Date Recei	ved	1/15/2016	Date	Complete	3/10/2016

Test Summary					
Test Specification	۱ ۱	Test Criteria	Test Result	Pass/Fail	
	Static Strength (Dorsal D-ring)	3600 Lbf <u>&gt;</u> 1 Minute	3639.6 Lbf	Pass	
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass	
ANSI Z359.11-2014	Adjuster Slippage	Slippage <u>&lt;</u> 1"	0.438"	Pass	
4.3.5	Tear Distance	Shall Not Tear a Distance Greater Than to Adjacent Eyelet	Did Not Tear Through	Pass	
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass	
	Static Strength (Dorsal D-ring)	3600 Lbf <u>&gt;</u> 1 Minute	3646.9 Lbf	Pass	
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass	
ANSI Z359.11-2014	Adjuster Slippage	Slippage <u>&lt;</u> 1"	0.298"	Pass	
4.3.5	Tear Distance	Shall Not Tear a Distance Greater Than to Adjacent Eyelet	Did Not Tear Through	Pass	
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass	
	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3639.1 Lbf	Pass	
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass	
ANSI Z359.11-2014	Adjuster Slippage	Slippage <u>&lt;</u> 1"	0.296"	Pass	
4.3.5	Tear Distance	Shall Not Tear a Distance Greater Than to Adjacent Eyelet	Did Not Tear Through	Pass	
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass	







FallTech Test Report							
Test Report Number	PC-0801	Date	3/11/2016	Rev		Rev Date	
Report Prepared For	FallTech				•		
Initiated By	Dan Redden	Test Specification		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.6, 4.3.7			
Base Part #	7087BQS	Description		Full Body Harness			
Proposed Part #	N/A	<b>Built By WI</b>	nom	Production	Production		No
Test Request #	PC-0801	Date Recei	ved	1/15/2016	Date	Complete	3/10/2016
-				1		1	
	Dynamic Performance	Peak Impact	Load	4742	2.0 Lbf		Pass
	Dorsal D-ring (Feet First)	<u>&gt;</u> 3600 Lbf					
	Dynamic Performance		l Not Release Test	Did Not	t Release		Pass
	Dorsal D-ring (Feet First)	Torso					
	Dynamic Performance		ended for <u>&gt;</u> 5	5 M	inutes		Pass
	Dorsal D-ring (Feet First)	Minutes					
ANSI Z359.11-2014	Dynamic Performance	Angle at Rest	: <u>&lt;</u> 30°	3	.1°		Pass
4.3.3	Dorsal D-ring (Feet First)	0	-				
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Indicator Sha Visibly and P	II be Deployed	-	Permanently loyed		Pass
	Dynamic Performance	Harness Stre	tch Shall Not	0	76"		Data
	Dorsal D-ring (Feet First)	Exceed 18"		8.	76		Pass
	Dynamic Performance	Peak Impact	Load	5000	) C I bf		Dage
	Dorsal D-ring (Feet First)	<u>&gt;</u> 3600 Lbf		5005	9.6 Lbf		Pass
	Dynamic Performance	Harness Shall Not Release Test		Did Not Release			Pass
	Dorsal D-ring (Feet First)	Torso		Dia Not Nelease		1 435	
	Dynamic Performance	Remain Susp	ended for <u>&gt;</u> 5	5 Minutes			Pass
	Dorsal D-ring (Feet First)	Minutes					
ANSI Z359.11-2014	Dynamic Performance	Angle at Rest	. < 30°	1.1°			Pass
4.3.3	Dorsal D-ring (Feet First)	, ingre ut nest	<u>-</u>				1 000
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Indicator Sha Visibly and P	II be Deployed	-	Permanently loyed		Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stree Exceed 18"	tch Shall Not	7	.8"		Pass
	Dynamic Performance	Peak Impact	Load	400	5.1 Lbf		Pass
	Dorsal D-ring (Feet First)	<u>&gt;</u> 3600 Lbf		4085	0.1 LUI		r d>>
	Dynamic Performance	Harness Shal	l Not Release Test		t Release		Pass
	Dorsal D-ring (Feet First)	Torso		Bid No	t Neleuse		1 435
	Dynamic Performance		ended for <u>&gt;</u> 5	5 M	inutes		Pass
	Dorsal D-ring (Feet First)	Minutes		5 101			. 100
ANSI Z359.11-2014	Dynamic Performance	Angle at Rest	t <u>&lt;</u> 30°	.	5°		Pass
4.3.3	Dorsal D-ring (Feet First)		-				
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Indicator Sha Visibly and P	Il be Deployed		Permanently loyed		Pass
	Dynamic Performance		tch Shall Not	ĥ	24"		Pass
	Dorsal D-ring (Feet First)	Exceed 18"		0.			1 000





### **FallTech Testing Laboratory**

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

Test Report Number	PC-0801	Date	3/11/2016	Rev		Rev Date		
Report Prepared For	FallTech							
Initiated By	Dan Redden	Test Specification		ANSI Z359.11-2014 4.3.5, 4.3.3, 4.3.6, 4.3.7				
Base Part #	7087BQS	Description		Full Body Harness				
Proposed Part #	N/A	Built By WI	nom	Production	the second s		BOM No	
Test Request #	PC-0801	Date Received		1/15/2016	Date	Complete 3/10/20		
ANSI 2359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently		Visibly and Permanently Deployed		Pass		
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently		Visibly and Permanently Deployed		Pass		
ANSI Z359.11-2014 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently		Visibly and Permanently Deployed		/ Pass		
ANSI Z359.11-2014 4.3.7	Lanyard Parking Attachment Element	Disengagement Load ≤ 120 Lbf		Passed	Tested and I under 0606		Pass	
		Cor	nclusion	and interest	2000	S. State of State	748.05	
New Addition of the second	FallTech P/N 7087	2000						

	Report Signatories and Approval		
Lab Quality Manager	Jay Sponholz	Date	3/11/2016
Witnessed by	Robert Forten	Date	3/22/2016



This laboratory is accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer to the joint ISO-ILAC-IAF Communique dated January 2009). FailTech Testing Laboratory allows for a +/- 5% tolerance on dynamic and static strength test results. 1

Exova 3883 East Eagle Drive Anaheim California USA 92807 T: +1 (714) 630-3003 F: +1 (714) 630-4443 E: sales@exova.com W: www.exova.com



Testing. Advising. Assuring.

April 27, 2017

FallTech Testing Laboratory 1306 S. Alameda Street Compton, CA 90221

Attention: Jay Sponholz Quality Manager

Subject:

Attestation of Witnessing TestingExova OCM Job #370708-1FallTech P.O.:OPENReport No.:PC-0801 HFBase Part No.7087BQSDescription:Full Body Harness

Dear Mr. Sponholz:

The purpose of this attestation is to attest to the fact that a representative of Exova OCM was on site at FallTech's facilities to confirm suitability of the equipment used, calibration status of the equipment and to witness testing performed by FallTech employees. Details of this visit are included below:

- Date of Testing:
  - March 30, 2017
- Exova OCM Test Witness:
  - Kevin Ton
- FallTech Test Operators:
  - Yesbet Sierra and Jay Sponholz
- Specification:

•

- ANSI Z359.11-2014; 4.3.4
- Equipment Calibration Interval
  - 1 year, except weights which are 5 years



#### 

Attached to this attestation is the test report generated by FallTech Testing Laboratory. Exova OCM test witness certifies the report accurately presents the testing performed on the samples identified.

Test Report #	Date	Base Part #	Description	Sample ID's	Results
				H1	
PC-0801 HF	3/30/2017	7087BQS	Full Body Harness	H2	Pass
				H3	

Test Witness Signature:	(Signed for and on behalf of	FExova-OCM)
Kevin Ton Test Technician Mechanical Laboratory	Kri Zu	OCM 072 QUALITY

Approval Signature:	(Signed for and on behalf of Exova-OCM)	
Thomas J. (Tom) Parsons Manager Quality / Technical Services	Infran	054 BLAPPENE

This attestation shall not be reproduced except in full, without the written approval of Exova-OCM. The laboratory has witnessed the testing the material / items supplied by the client as sampled by the client. The testing is not within Exova OCM's LA.B scope of testing and was not performed at Exova OCM.



FallTech Testing Laboratory Attestation Number: 370708-1 Revision Letter: Original Page 2 of 2

### **FallTech Testing Laboratory**



FallTech Test Report							
Test Report No.	PC-0801 HF	Rpt. Date 3/31/2017	Rpt. Rev	Rev Date			
Report Prepared For	FallTech						
Initiated By	Dan Redden	Redden Test Specification(s) ANSI Z359.11-2014; 4.3.4					
Part No.	7087BQS	Part No. Revision A		A			
Part Description	Full Body Harness						
Test Request No.	PC-0801 HF Date Complete 3/30/2017			3/30/2017			
Test Operator(s)	Yesbet Sierra / Jay Sponholz						
		Material/Sample Identification					
Sample ID		Descriptior	ı				
H1	Full Body Harness						
H2	Full Body Harness						
H3	Full Body Harness						
Test Summary							
Test Specification	Те	st Criteria	Test Result	Pass/Fail			
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load <u>&gt;</u> 3,600 Lbf	3449.5 Lbf	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for <u>&gt;</u> 5 Minutes	5 Minutes	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest <u>&lt;</u> 30°	21.3°	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass			
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load <u>&gt;</u> 3,600 Lbf	3921.1 Lbf	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for <u>&gt;</u> 5 Minutes	5 Minutes	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest <u>&lt;</u> 30°	1.4°	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass			



## **FallTech Testing Laboratory**



		FallTech Test Repor				
Test Report No.	PC-0801 HF	Rpt. Date 3/31/2017	Rpt. Rev	Rev Date		
Report Prepared For	FallTech					
nitiated By	Dan Redden Test Specification(s) ANSI Z359.11-2014; 4.3.4			4		
Part No.	7087BQS		Part No. Revision A			
Part Description	Full Body Harness					
Fest Request No.	PC-0801 HF		Date Complete	3/30/2017		
	Trailed and the second	Test Summary	The sub- State of the state of the			
Test Specification	Te	est Criteria	Test Result	Pass/Fail		
ANSI Z359.11-2014 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact Load ≥ 3,600 Lbf	3282.7 Lbf	*		
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for $\geq$ 5 Minute	s 5 Minutes	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	3.1°	Pass		
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass		
		Conclusion				
	FallTech P/N 7087BQ	S Rev. A meets the requirements of AN	SI Z359.11-2014. 4.3.4			
		Test Exceptions				
* Harness has been dyna		o forces of 5,000 Lbs. or more. Energy qual to or greater than the 3,600 Lbs.		nt to the harness prevente		
	Į.	Report Signatories and Approv	al			
Lab Quality Manager	Jay Sponholz	Sponholz	Date	3/31/2017		
Witnessed by	Kevin Ton	L	Date	5/5/2017		

