

Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B0427188

Declaration Date

4/27/2023

Tested Item #

8142QCSCM

FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M,
QC Legs and Chest

Additional Items Conforming Under this Declaration:

8142FDQC2X 8142FDQCM 8142FDQCXS 8142QCSCM
8142FDQC3X 8142FDQCS 8142QC2X3X 8142QCXS
8142FDQCL 8142FDQCXL 8142QCLXL

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

ANSI Z359.11-2021

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

Level 1: FallTech Lab
Outside the Scope of
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab
Within the Scope of
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab
accredited to
ISO/IEC Standard 17025:2005

Supporting
Documentation

PC-2824

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

4/27/2023



International Accreditation Service, Inc
3060 Saturn St, Ste 100
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594
ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech

FallTech Test Report

Test Report No.	PC-2824	Rpt. Date	4/26/2023	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Zachary Winters	Test Specification(s)		ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
Part No.	8142QCSCM	Part No. Revision			D		
Part Description	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest						
Test Request No.	PC-2824	Date Complete			4/25/2023		
Test Operator(s)	Yesbet Sierra / Jay Sponholz						

Material/Sample Identification

Sample ID	Description
6936713	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936725	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936718	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936716	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936722	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936720	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936717	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936712	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936719	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936711	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936696	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936695	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936720	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936722	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest
6936716	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest

Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3625.5 Lbf Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release Pass
	Adjuster Slippage	Slippage \leq 1"	0.25" Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3642.6 Lbf Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release Pass
	Adjuster Slippage	Slippage \leq 1"	0.20" Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf \geq 1 Minute	3658.2 Lbf Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release Pass
	Adjuster Slippage	Slippage \leq 1"	0.22" Pass
	Tear Distance (Buckle)	Shall Not Tear > 1"	Did Not Tear Through Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear Pass

FallTech Test Report

Test Report No.	PC-2824	Rpt. Date	4/26/2023	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Zachary Winters	Test Specification(s)		ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
Part No.	8142QCSCM	Part No. Revision			D		
Part Description	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest						
Test Request No.	PC-2824	Date Complete			4/25/2023		

Test Summary Continued

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3627.8 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear $>$ 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3639.5 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear $>$ 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Side D-rings)	3600 Lbf \geq 1 Minute	3643.9 Lbf	Pass
	Hold Test Torso	Shall Not Release Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage \leq 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear $>$ 1"	Did Not Tear Through	Pass
	Tearing (Straps)	Shall Not Show Any Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load \geq 3600 Lbf	4853.3 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	1.2°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	8.9"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load \geq 3600 Lbf	4727.6 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	1.7°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	9.3"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load \geq 3600 Lbf	4630.3 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	1.5°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
	Harness Stretch	Shall Not Exceed 18"	9.7"	Pass

FallTech Test Report

Test Report No.	PC-2824	Rpt. Date	4/26/2023	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Zachary Winters	Test Specification(s)		ANSI Z359.11-2021: 4.3.3, 4.3.4, 4.3.5, 4.3.6			
Part No.	8142QCSM	Part No. Revision			D		
Part Description	FT-Iron FBH 3D Standard Non-Belted, Dual Size S/M, QC Legs and Chest						
Test Request No.	PC-2824	Date Complete			4/25/2023		

Test Summary Continued

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall	72" Free fall 2141.0 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	4.1°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall	72" Free fall 2141.2 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	3.9°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall	72" Free fall 2645.4 Lbf	Pass
	Fall Arrest	Shall Not Release Torso	Did Not Release	Pass
	Post Drop Angle	Angle at Rest \leq 30°	10.2°	Pass
	Impact Indicator	One Indicator Shall Deploy	Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Doral D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

Conclusion

Based upon the samples provided to the Lab:
 FallTech P/N 8142QCSM Rev. D meets the requirements of ANSI Z359.11-2021

Report Signatories and Approval

Lab Quality Manager		Date	4/26/2023
----------------------------	---	-------------	-----------