

# Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St Compton, CA 90221 (800) 719-4619

Declaration #

B0804157a

Declaration Date

8/4/2021

Tested Item #

8124BFDQCM

FT-One FBH 1D+FD Climbing Non-Belted, Medium, QC  
Legs/QC Chest

Additional Items Conforming Under this Declaration:

8124BFDQCXS 8124BFDQCXL 8124B4DQCXS 8124B4DQCL 8124B4DQC3X

8124BFDQCS 8124BFDQC2X 8124B4DQCS 8124B4DQCXL

8124BFDQCL 8124BFDQC3X 8124B4DQCM 8124B4DQC2X

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

ANSI Z359.11-2021

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Level 3

Level 1: FallTech Lab  
Outside the Scope of  
ISO/IEC Standard 17025:2005

Level 2: FallTech Lab  
Within the Scope of  
ISO/IEC Standard 17025:2005

Level 3: Independent 3rd Party Lab  
accredited to  
ISO/IEC Standard 17025:2005

Supporting  
Documentation

PC-2325

Authorized Signature

Name

Zachary Winters

Title

Engineering Manager

Date

4/18/2023



International Accreditation Service, Inc  
3060 Saturn St, Ste 100  
Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594  
ISO/IEC 17025:2017  
Alexander Andrew Inc dba FallTech

## FallTech Test Report

<b>Test Report No.</b>	PC-2325	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	8124BFDQCM	<b>Part No. Revision</b>	A				
<b>Part Description</b>	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest						
<b>Test Request No.</b>	PC-2325	<b>Date Complete</b>	8/3/2021				
<b>Test Operator(s)</b>	Yesbet Sierra / Jay Sponholz						

### Material/Sample Identification

Sample ID	Description
SST1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
SST2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
SST3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
SSTS1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
SSTS2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
SSTS3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
DPT1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
DPT2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
DPT3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
HF1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
HF2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
HF3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
DPTS1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
DPTS2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
DPTS3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
I1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
I2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest
I3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest

### Test Summary

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3646.6 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass



## FallTech Test Report

<b>Test Report No.</b>	PC-2325	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	8124BFDQCM	<b>Part No. Revision</b>	A				
<b>Part Description</b>	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest						
<b>Test Request No.</b>	PC-2325	<b>Date Complete</b>	8/3/2021				

### Test Summary (Continued)

Test Specification	Test Criteria		Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3649.9 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Dorsal D-ring)	3600 Lbf $\geq$ 1 Minute	3644.0 Lbf	Pass
	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.0"	Pass
	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Sternal D-ring)	3600 Lbf $\geq$ 1 Minute	3631.1 Lbf	Pass
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.16"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass
ANSI Z359.11-2021 4.3.5	Static Strength (Sternal D-ring)	3600 Lbf $\geq$ 1 Minute	3629.6 Lbf	Pass
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.18"	Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass

## FallTech Test Report

<b>Test Report No.</b>	PC-2325	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	8124BFDQCM	<b>Part No. Revision</b>	A				
<b>Part Description</b>	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest						
<b>Test Request No.</b>	PC-2325	<b>Date Complete</b>	8/3/2021				

### Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.5	Static Strength (Sternal D-ring)	3600 Lbf $\geq$ 1 Minute	3630.7 Lbf Pass
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release Pass
	Adjuster Slippage	Slippage $\leq$ 1"	0.29" Pass
	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through Pass
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	4703.5 Lbf Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq$ 30°	2.1° Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	10.4" Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	5210.3 Lbf Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest $\leq$ 30°	2.7° Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.9" Pass

## FallTech Test Report

<b>Test Report No.</b>	PC-2325	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	8124BFDQCM	<b>Part No. Revision</b>	A				
<b>Part Description</b>	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest						
<b>Test Request No.</b>	PC-2325	<b>Date Complete</b>	8/3/2021				

### Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4975.8 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	3.4°	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	14.0"	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact ≥ 3,600 Lbf or 72" Free Fall	72" Free fall 1946.3 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	28.8°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact ≥ 3,600 Lbf or 72" Free Fall	72" Free fall 1585.1 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	4.5°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass

## FallTech Test Report

<b>Test Report No.</b>	PC-2325	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	8124BFDQCM	<b>Part No. Revision</b>	A				
<b>Part Description</b>	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest						
<b>Test Request No.</b>	PC-2325	<b>Date Complete</b>	8/3/2021				

### Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail	
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact $\geq$ 3,600 Lbf or 72" Free Fall	72" Free fall 1802.2 Lbf	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest $\leq$ 30°	12.3°	Pass
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	3834.5 Lbf	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest $\leq$ 50°	27.2°	Pass
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.0"	Pass
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load $\geq$ 3600 Lbf	3785.6 Lbf	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for $\geq$ 5 Minutes	5 Minutes	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest $\leq$ 50°	26.9°	Pass
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	12.0"	Pass



## FallTech Test Report

<b>Test Report No.</b>	PC-2325	<b>Rpt. Date</b>	8/4/2021	<b>Rpt. Rev</b>		<b>Rev Date</b>	
<b>Report Prepared For</b>	FallTech						
<b>Initiated By</b>	Dan Redden	<b>Test Specification(s)</b>	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6				
<b>Part No.</b>	8124BFDQCM	<b>Part No. Revision</b>	A				
<b>Part Description</b>	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, QC Legs/QC Chest						
<b>Test Request No.</b>	PC-2325	<b>Date Complete</b>	8/3/2021				


### Test Summary (Continued)

Test Specification	Test Criteria	Test Result	Pass/Fail
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	3848.1 Lbf Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release Pass
	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes Pass
	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest ≤ 50°	29.0° Pass
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed Pass
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	13.1" Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed Pass
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed Pass

### Conclusion

Based upon the samples provided to the Lab:  
 FallTech P/N 8124BFDQCM Rev. A meets the requirements of ANSI Z359.11-2021

### Report Signatories and Approval

Lab Quality Manager		Date	8/4/2021
Witnessed by	Not Required	Date	N/A

