Declaration of Conformity

In Accordance with ANSI/ISEA 125-2014 and ANSI/ASSP Z359.7-2019



Alexander Andrew, Inc. 1306 S. Alameda St. Compton, CA 90221 (800) 719-4619

Declaration #

B0804159

Declaration Date

8/5/2021

Tested Item #

8128BFDM

FT-One FBH 1D+FD Climbing Non-Belted, Medium, TB **Legs/QC Chest**

Additional Items Conforming Under this Declaration:

8128BFDXS 8128BFDXL 8127BFDXS

8127BFDL 8127BFD3X

8128BFDS 8128BFD2X 8127BFDS

8127BFDXL

8128BFDL

8128BFD3X 8127BFDM 8127BFD2X

Alexander Andrew, Inc. declares that the product(s) listed above is in conformity with the requirements of the following product standard(s):

Λľ	บรเ	72	50	11	」っつ	റാ	1

Conformity Assessment Method in accordance with ANSI/ISEA 125-2014

Level 1

Level 2

Χ

Level 3

Level 1: FallTech Lab Outside the Scope of ISO/IEC Standard 17025:2005

Level 2: FallTech Lab Within the Scope of ISO/IEC Standard 17025:2005 Level 3: Independent 3rd Party Lab accredited to ISO/IEC Standard 17025:2005

Supporting Documentation

PC-2326

Authorized Signature

Zachary Winters Name

Engineering Manager

Date 8/5/2021



International Accreditation Service, Inc 3060 Saturn St, Ste 100

Brea, CA 92821 +1 562-364-8201

FallTech Lab - TL-594

ISO/IEC 17025:2017

Alexander Andrew Inc dba FallTech





FallTech Test Report							
Test Report No.	PC-2326	Rpt. Date	8/5/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specific	cation(s)	ANSI Z35	9.11-2021: 4	4.3.5, 4.3.3,	4.3.4, 4.3.6
Part No.	8124BFDM			Part No. Re	evision	Α	
Part Description	FT-One Fit FBH 1D + FD Cli	mbing Non-belt	ed, Medium, Tl	B Legs/QC Cl	nest		
Test Request No.	PC-2326			Date Comp	lete	8/4/2021	
Test Operator(s)	Yesbet Sierra / Jay Sponh	resbet Sierra / Jay Sponholz					

	Material/Sample Identification
Sample ID	Description
SST1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
SST2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
SST3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
SSTS1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
SSTS2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
SSTS3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
DPT1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
DPT2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
DPT3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
HF1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
HF2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
HF3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
DPTS1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
DPTS2	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
DPTS3	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
I1	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
12	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest
13	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest

Test Summary									
Test Specification	Test (Criteria	Test Result	Pass/Fail					
	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3638.4 Lbf	Pass					
ANSI Z359.11-2021	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass					
4.3.5	Adjuster Slippage	Slippage <u><</u> 1"	0.0"	Pass					
4.5.5	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass					
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass					





FallTech Test Report							
Test Report No.	PC-2326	Rpt. Date	8/5/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specific	cation(s)	ANSI Z359	9.11-2021: 4	4.3.5, 4.3.3, 4	1.3.4, 4.3.6
Part No.	8124BFDM			Part No. Re	evision	Α	
Part Description	FT-One Fit FBH 1D + FD Clin	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest					
Test Request No.	PC-2326			Date Comp	lete	8/4/2021	

Test Summary (Continued)							
Test Specification	Test	Criteria	Test Result	Pass/Fail			
	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3645.0 Lbf	Pass			
ANGLES 14 0004	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
ANSI Z359.11-2021 4.3.5	Adjuster Slippage	Slippage < 1"	0.0"	Pass			
4.5.5	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass			
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass			
	Static Strength (Dorsal D-ring)	3600 Lbf ≥ 1 Minute	3645.0 Lbf	Pass			
ANG 7250 44 2024	Static Strength (Dorsal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
ANSI Z359.11-2021 4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.0"	Pass			
4.3.3	Tear Distance (Buckle)	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass			
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass			
	Static Strength (Sternal D-ring)	3600 Lbf ≥ 1 Minute	3648.5 Lbf	Pass			
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
ANSI Z359.11-2021 4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.0"	Pass			
4.5.5	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass			
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass			
	Static Strength (Sternal D-ring)	3600 Lbf ≥ 1 Minute	3646.3 Lbf	Pass			
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
ANSI Z359.11-2021 4.3.5	Adjuster Slippage	Slippage ≤ 1"	0.0"	Pass			
4.3.5	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass			
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass			





	FallTech Test Report							
Test Report No.	PC-2326	Rpt. Date	8/5/2021	Rpt. Rev		Rev Date		
Report Prepared For	FallTech							
Initiated By	Dan Redden	Test Specific	ation(s)	ANSI Z359	9.11-2021: 4	1.3.5, 4.3.3, 4	1.3.4, 4.3.6	
Part No.	8124BFDM			Part No. Re	evision	Α		
Part Description	FT-One Fit FBH 1D + FD Cli	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest						
Test Request No.	PC-2326	C-2326 Date Complete 8/4/2021						

	Test Summary (Continued)							
Test Specification	Test	Criteria	Test Result	Pass/Fail				
	Static Strength (Sternal D-ring)	3600 Lbf ≥ 1 Minute	3642.4 Lbf	Pass				
	Static Strength (Sternal D-ring)	Harness Shall Not Release Test Torso	Did Not Release	Pass				
ANSI Z359.11-2021 4.3.5	Adjuster Slippage	Slippage <u><</u> 1"	0.0"	Pass				
4.3.3	Tear Distance	Shall Not Tear a Distance > 1" or Adjacent Eyelet	Did Not Tear Through	Pass				
	Tearing	Straps Shall Not Show Any Signs of Tearing	Did Not Tear	Pass				
	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	5030.0 Lbf	Pass				
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass				
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for <u>></u> 5 Minutes	5 Minutes	Pass				
4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	2.6°	Pass				
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass				
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.4"	Pass				
	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	5200.1 Lbf	Pass				
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass				
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for <u>></u> 5 Minutes	5 Minutes	Pass				
4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	3.3°	Pass				
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass				
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	11.8"	Pass				





FallTech Test Report							
Test Report No.	PC-2326	Rpt. Date	8/5/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specific	cation(s)	ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8124BFDM			Part No. Re	evision	Α	
Part Description	FT-One Fit FBH 1D + FD Cli	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest					
Test Request No.	PC-2326			Date Comp	lete	8/4/2021	

Test Summary (Continued)							
Test Specification	Test	Criteria	Test Result	Pass/Fail			
	Dynamic Performance Dorsal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	4908.7 Lbf	Pass			
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
ANSI Z359.11-2021 4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass			
4.3.3	Dynamic Performance Dorsal D-ring (Feet First)	Angle at Rest ≤ 30°	2.8°	Pass			
	Dynamic Performance Dorsal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass			
	Dynamic Performance Dorsal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	13.4"	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall	72" Free fall 2362.7 Lbf	Pass			
ANG 7070 44 0004	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for <u>></u> 5 Minutes	5 Minutes	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	7.3°	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact \geq 3,600 Lbf or 72" Free Fall	72" Free fall 2191.4 Lbf	Pass			
ANG 7070 44 0004	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	7.1°	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass			





FallTech Test Report							
Test Report No.	PC-2326	Rpt. Date	8/5/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specific	cation(s)	ANSI Z359	9.11-2021: 4	4.3.5, 4.3.3, 4	1.3.4, 4.3.6
Part No.	8124BFDM			Part No. Re	evision	Α	
Part Description	FT-One Fit FBH 1D + FD Cli	T-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest					
Test Request No.	PC-2326			Date Comp	lete	8/4/2021	·

Test Summary (Continued)							
Test Specification	Test	Criteria	Test Result	Pass/Fail			
	Dynamic Performance Dorsal D-ring (Head First)	Peak Impact <u>></u> 3,600 Lbf or 72" Free Fall	72" Free fall 1614.3 Lbf	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
ANSI Z359.11-2021 4.3.4	Dynamic Performance Dorsal D-ring (Head First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	Angle at Rest ≤ 30°	4.3°	Pass			
	Dynamic Performance Dorsal D-ring (Head First)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	3470.7 Lbf	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
ANCI 7250 44 2024	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass			
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest ≤ 50°	27.7°	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	9.6"	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	3742.0 Lbf	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
ANSI Z359.11-2021	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for <u>></u> 5 Minutes	5 Minutes	Pass			
4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest ≤ 50°	26.2°	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	8.6"	Pass			



FallTech Testing Laboratory

1306 S. Alameda Street, Compton, CA 90221-4803 Tel: (323) 752-0060 www.falltech.com

FallTech Test Report							
Test Report No.	PC-2326	Rpt. Date	8/5/2021	Rpt. Rev		Rev Date	
Report Prepared For	FallTech						
Initiated By	Dan Redden	Test Specification(s)		ANSI Z359.11-2021: 4.3.5, 4.3.3, 4.3.4, 4.3.6			
Part No.	8124BFDM			Part No. Re	evision	on A	
Part Description	FT-One Fit FBH 1D + FD Climbing Non-belted, Medium, TB Legs/QC Chest						
Test Request No.	PC-2326		Date Comp	8/4/2021			

Test Summary (Continued)							
Test Specification	Test	Criteria	Test Result	Pass/Fail			
ANSI Z359.11-2021 4.3.3	Dynamic Performance Sternal D-ring (Feet First)	Peak Impact Load ≥ 3600 Lbf	3838.8 Lbf	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	Harness Shall Not Release Test Torso	Did Not Release	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	Remain Suspended for ≥ 5 Minutes	5 Minutes	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	Angle at Rest ≤ 50°	27.7°	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	At Least One Fall Arrest Indicator Shall be Deployed Visibly and Permanently	Visibly and Permanently Deployed	Pass			
	Dynamic Performance Sternal D-ring (Feet First)	Harness Stretch Shall Not Exceed 18"	7.7"	Pass			
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass			
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass			
ANSI Z359.11-2021 4.3.6	Fall Arrest Indicator Test (Dorsal D-ring)	At Least One Fall Arrest Indicator Shall Deploy	Visibly and Permanently Deployed	Pass			

Conclusion

Based upon the samples provided to the Lab:

FallTech P/N 8128BFDM Rev. A meets the requirements of ANSI Z359.11-2021

Report Signatories and Approval						
Lab Quality Manager	Jay Sponholz		8/5/2021			
Witnessed by	Not Required	Date	N/A			