

## Cut, Abrasion, Puncture, Impact, and Flame Resistant Grain Goatskin Mig/Tig Welding Gloves

### DESCRIPTION

This premium-grade grain goatskin leather glove, both oil and water-resistant, is further enhanced by a thin Aralene® (enhanced aramid fiber) liner. The back of the hand and fingers are protected by a flexible layer of TPR impact protection. Every seam is sewn with black DuPont™ Kevlar® fiber thread for added durability and heat resistance. Each pair is individually hang-tagged for retail sale.



### INDUSTRY

Construction	MIG/TIG Welding
Fabrication	Oil and Gas
Manufacturing	Utilities
Metal Fabrication	

### FEATURES

- Premium-grade grain goatskin offers ultimate dexterity
- Proprietary oil/water resistant manufacturing process to ensure longer lasting benefits over a spray-on treatment
- Sewn with black aramid fiber for added durability and heat resistance
- Thin sewn-in Aralene® liner inside the entire glove and cuff offers great dexterity, cut resistance, and heat resistance
- Soft, flexible, TPR impact protection over the fingers and metacarpal bones provides tough protection
- Reinforced leather patch on the side of the hand
- Straight thumb for a better grip
- 4.5 inch long split leather gauntlet cuff allows for easy donning and removal plus extra forearm protection
- ANSI/ISEA 105 Cut Level A8

### ITEM CIA200MTG SIZES 8(M)-11(2XL)

- ASTM F2992-15 Results = 5,225 grams
- ANSI/ISEA 105 Abrasion Level 4
- ANSI/ISEA 105 Puncture Level 4
- ANSI/ISEA 105 Puncture Results: 101 Newtons
- ANSI/ISEA 138 Impact Level (Overall): 2
- EN 388 Levels: 3X43F
- Tested to ASTM F2675
- Arc Rating (ATPV) = 35 Cal/cm<sup>2</sup>
- Heat Attenuation Factor (HAF) = 93%
- NFPA 70E Arc Flash PPE Category: 3



### SPECIFICATIONS

SHELL	SHELL COLOR	GRADE	LINER	THUMB	CUFF	ANSI CUT	ASTM F2992-15 RESULTS	ANSI ABRASION	ANSI PUNCTURE	PUNCTURE RESULTS
Grain Goatskin	Black	Premium	Aralene®	Straight	Gauntlet	Level A8	5,225 Grams	Level 4	Level 4	101 Newtons
ANSI/ISEA 138 IMPACT LEVEL (FINGERS/THUMB)	ANSI/ISEA 138 IMPACT LEVEL (KNUCKLES)	ANSI/ISEA 138 IMPACT LEVEL (OVERALL)	EN 388 LEVELS	ARC RATING (ATPV)	NFPA 70E ARC-FLASH PPE CATEGORY	HEAT ATTENUATION FACTOR (HAF)				
2	2	2	3X43F	35 Cal/cm <sup>2</sup>	3	93%				

### PACKAGING

	QUANTITY	8(M)	9(L)	10(XL)	11(2XL) *6 PK/CASE
PAIR UPC	1	810033291357	810033291364	810033291371	810033291388
INNER PACK GTIN	12/PACK	10810033291354	10810033291361	10810033291378	10810033291385
CASE GTIN	3 PK/CASE*	30810033291358	30810033291365	30810033291372	20810033291382
CASE WEIGHT (IN POUNDS)		29.35	31.45	34.3	74.4

13915 Radium St NW  
Ramsey, MN 55303

763-450-0110  
Sales@GlobalGlove.com

GlobalGlove.com

  
**Global Glove**  
& Safety Manufacturing, Inc.