

Low Temperature Cut, Impact, Abrasion, and Puncture Resistant Gloves

DESCRIPTION

These insulated gloves are constructed with a 10-gauge Tuffalene® UHMWPE shell with a brushed acrylic terry cloth interior for excellent warmth and comfort. The shell is enhanced with TPU impact protection and coated palm with foam rubber latex which provides excellent grip, abrasion resistance, and puncture resistance.



INDUSTRY

Automotive	Farming
Carpentry	Landscaping
Cold Storage	Material Handling
Construction	Warehousing

FEATURES

- One-piece enhanced Tuffalene® UHMWPE seam-free shell with brushed acrylic terry cloth liner for warmth and comfort
- Foam natural rubber latex-coated palm for grip plus abrasion and puncture resistance
- Soft, flexible, TPU impact protection over the fingers and metacarpal bones provides tough protection
- Overcast color on hem for easy size identification
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use

SPECIFICATIONS

SHELL	SHELL COLOR	GAUGE	LINER	COATING	COATING COLOR	COATING TYPE	CUFF	FINISH	IMPACT PROTECTION
Tuffalene® UHMWPE	White and Blue	10-Gauge	Acrylic Terry Cloth	Rubber Latex	Black	Palm	Knit Wrist	Foam	TPU

ANSI CUT	ASTM F2992-15 RESULTS	ANSI ABRASION	ANSI PUNCTURE	PUNCTURE RESULTS	ANSI/ISEA IMPACT	EN 388 LEVELS
Level A4	1,598 Grams	Level 3	Level 3	80 Newtons	Level 1	2X42DP

PACKAGING

	QUANTITY	7(S)	8(M)	9(L)	10(XL)
PAIR UPC	1	NA	NA	NA	NA
INNER PACK UPC	12/PACK	816368029061	816368029078	816368029085	816368029092
CASE GTIN	6 PK/CASE	10816368029068	10816368029075	10816368029082	10816368029099
CASE WEIGHT (IN POUNDS)		26.8	28	33.3	34.4
OVERCAST COLOR		Red	Green	Brown	Black

ITEM CIA300INT

SIZES 7(S)-10(XL)

- ANSI/ISEA 105 Cut Level A4
- ASTM F2992-15 Results = 1,598 grams
- ANSI/ISEA 105 Abrasion Level 3
- ANSI/ISEA 105 Puncture Level 3
- ANSI/ISEA 105 Puncture Results: 80 Newtons
- ANSI/ISEA 138 Impact Level (Overall): 1
- ANSI/ISEA 138 Impact Level (Knuckles): 1
- ANSI/ISEA 138 Impact Level (Fingers/Thumb): 2
- EN 388 Levels: 2X42DP

