



# HAND PROTECTION

## Cut, Abrasion, Puncture, and Flame-Resistant Arc-Flash Gloves with a Mach Finish Neoprene Bi-Polymer Coating

### DESCRIPTION

These premium cut and flame-resistant gloves feature a flexible, 15-gauge Aralene® (enhanced aramid fiber) shell further enhanced by a black Mach Finish coated palm made from neoprene bi-polymers. The knit wrist provides wrist support and helps prevent gloves from slipping off during use.

### INDUSTRY

|                   |                      |
|-------------------|----------------------|
| Automotive        | Mining               |
| Construction      | Utilities            |
| Metal Fabrication | Oil and Gas Refining |
| Material Handling |                      |



### FEATURES

- 15-gauge enhanced Aralene® shell offers bare hand sensitivity, cut resistance, and heat resistance
- Mach Finish neoprene bi-polymer palm provides flame-resistance and is excellent for grip in wet and oily situations as well as abrasion resistance
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use
- ANSI/ISEA 105 Cut Level A5
- ASTM F2992-15 Results = 2,748 grams
- ANSI/ISEA 105 Abrasion Level 3

### ITEM CR509

### SIZES 7(S)-11(2XL)

- ANSI/ISEA 105 Puncture Level 4
- ANSI/ISEA 105 Puncture Results: 114 Newtons
- Tested to ASTM F2675
- Arc Rating (ATPV) = 12.4 Cal/cm<sup>2</sup>
- Heat Attenuation Factor (HAF) = 80.4%
- NFPA 70E Arc-Flash PPE Category 2
- EN 388 Levels: 3X42D
- EN 407 Levels: X1212X



### SPECIFICATIONS

| SHELL         | GAUGE         | SHELL COLOR      | COATING                  | COATING TYPE                  | COATING COLOR                   | FINISH        | CUFF          | ANSI CUT | ASTM F2992-15 RESULTS |
|---------------|---------------|------------------|--------------------------|-------------------------------|---------------------------------|---------------|---------------|----------|-----------------------|
| Aralene®      | 15-Gauge      | Green            | Neoprene Bi-Polymer      | Palm                          | Black                           | Mach Finish   | Knit Wrist    | Level A5 | 2,748 Grams           |
| ANSI ABRASION | ANSI PUNCTURE | PUNCTURE RESULTS | ARC RATING (ATPV)        | HEAT ATTENUATION FACTOR (HAF) | NFPA 70E ARC-FLASH PPE CATEGORY | EN 388 LEVELS | EN 407 LEVELS |          |                       |
| Level 3       | Level 4       | 114 Newtons      | 12.4 Cal/cm <sup>2</sup> | 80.4%                         | 2                               | 3X42D         | X1212X        |          |                       |

### PACKAGING

|                         | QUANTITY  | 7(S)           | 8(M)           | 9(L)           | 10(XL)         | 11(2XL)        |
|-------------------------|-----------|----------------|----------------|----------------|----------------|----------------|
| PAIR UPC                | 1         | NA             | NA             | NA             | NA             | NA             |
| INNER PACK UPC          | 12/PACK   | 816368023182   | 816368023199   | 816368023205   | 816368023212   | 810033292231   |
| CASE GTIN               | 6 PK/CASE | 10816368023189 | 10816368023196 | 10816368023202 | 10816368023219 | 10810033292238 |
| CASE WEIGHT (IN POUNDS) |           | 14.5           | 16             | 18.5           | -              | -              |

13915 Radium St NW  
Ramsey, MN 55303

763-450-0110  
Sales@GlobalGlove.com

GlobalGlove.com

