



HAND PROTECTION

Palm Dipped Cut, Abrasion, and Puncture Resistant Vend-Pack Gloves

DESCRIPTION

This seamless 13-gauge glove has a comfortable Aralene® (enhanced aramid fiber) shell. The shell is enhanced by a foam nitrile dipped palm. Each pair of gloves is packaged for vending machines.



INDUSTRY

Glass Processing	Construction
Bottle Handling	Metal Fabrication
Automotive Industry	Metal Stamping
Aerospace Industry	

FEATURES

- Aralene® (enhanced aramid fiber) shell offers cut resistance, heat resistance and dexterity
- Foam nitrile provides excellent dry, wet, and oily grip with breathability
- Machine washable
- Overcast color on hem for easy size identification
- Knit wrist cuff offers users a secure, comfortable fit and prevents gloves from slipping off during use

ITEM CR609-VP

SIZES 7(S)-11(2XL)

- ANSI/ISEA 105 Cut Level A4
- ASTM F2992-15 Results = 2,117 grams
- ANSI/ISEA 105 Abrasion Level 4
- ANSI/ISEA 105 Puncture Level 3
- ANSI/ISEA 105 Puncture Results: 65 Newtons
- EN 388 Levels: 4X21D



SPECIFICATIONS

SHELL	GAUGE	SHELL COLOR	COATING TYPE	COATING COLOR	COATING	CUFF	FINISH	MACHINE WASHABLE	VEND-PACK
Aralene®	13-Gauge	Yellow/Black	Palm	Black	Nitrile	Knit Wrist	Foam	Yes	Yes
ANSI CUT	ASTM F2992-15 RESULTS	ANSI ABRASION	ANSI PUNCTURE	PUNCTURE RESULTS	EN 388 LEVELS				
Level A4	2,117 Grams	Level 4	Level 3	65 Newtons	4X21D				

PACKAGING

	QUANTITY	7(S)	8(M)	9(L)	10(XL)	11(2XL)
PAIR UPC	1	816368024974	816368024981	816368024998	816368025001	816368025018
INNER PACK GTIN	12/PACK	10816368024971	10816368024988	10816368024995	10816368025008	10816368025015
CASE GTIN	6 PK/CASE	20816368024978	20816368024985	20816368024992	20816368025005	20816368025012
CASE WEIGHT (IN POUNDS)		9	9.5	10	10.5	11
OVERCAST COLOR		Red	Green	Brown	Black	Light Blue

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
Sales@GlobalGlove.com

GlobalGlove.com


Global Glove
& Safety Manufacturing, Inc.