

CR609, CR639

Style	Sizes	Kevlar® Construction	Protection
CR609	7,8,9,10,11	The Tsunami Grip Tuff ™ Hybrid CR609 is a 13-gauge seamless knit glove that represents the latest development in high performance, cut-resistant fiber technology. The superior cut protection comes from an engineered yarn using a propriety wrapping process. The combination of Kevlar® and high strength fiberglass fibers combine to give a European EN 388 level 5 cut resistance. High dexterity 13-gauge glove. 1525 grams on American ASTM F-1790 for American level 4. The Hybrid also uses the propriety two step nitrile that gives grip similar to foam/air injected	Offers cut resistance level ASTM level 4 EN level 5 Cut protection.
CR639	7,8,9,10	nitrile but will not saturate through the coating. CR639 is a 3/4 dipped version for more back of the hand protection sizes (7 S to 10 XL)	1

Applications:

Industrial protection handling sharp materials with glass, sheet metal or razor sharp steel. Auto assembly, part assembly and handling sharp edge objects.

Phone:763-450-0110

Fax: 763-450-0990

Sales@globalglove.com Global Glove & Safety Manufacturing Inc.

Qualities:

•Excellent tactile dexterity and cut protection

•High cut resistance, ASTM level 4

•Tsunami Tuff™ nitrile gives outstanding grip w/o oils saturating through.

•Machine washable

•CR309 same as above with excellent rubber grip



Global Glove & Safety Mfg Inc 13915 Radium St. NW Ramsey, MN 55303