



**PYRAMEX**  
Perform At Your Peak™

**carhartt** 

**Carthage®** **ANSI CSA**



VENTED  
FRAME



INCLUDES  
STRAP



FOAM  
PADDING



Indirect vented foam padded carriage

Interchangeable temples/strap are included

Available in a Carhartt polybag

Polybag Part No.	Black and Tan Frame	
CHB410DTP ●●	AF	Clear
CHB418DTP ●●	AF	Sandstone Bronze
CHB420DTP ●●	AF	Gray
Polybag Part No.	Realtree Xtra® Camo Frame	
CHRT410DTP ●●	AF	Clear
CHRT420DTP ●●	AF	Gray



Polybags

There's more to see at  
**PYRAMEXSAFETY.COM**  
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ (●) and Canadian (CSA Z94.3) (◐) standards. All lenses provide 99% protection from harmful UV rays and are hard coated polycarbonate scratch-resistant unless otherwise noted.



**PYRAMEX**  
Perform At Your Peak™



carhartt

## Carthage®

### General Specifications

Weight: 43.7 gm  
 Bridge: 15 mm  
 Lens base: 8 curve  
 Lens size diagonal: 68 mm  
 Lens size vertical: 40 mm  
 Lens thickness: 2.0 mm  
 Overall length (lens - tip): 130 mm  
 Overall width (hinge - hinge): 134 + 1 mm  
 Closest point between temple tips: 80 + 5 mm  
 Closest point between lens: 17 mm

### Materials

Lens: polycarbonate  
 Closed cell foam: nylon and ethylene-vinyl acetate (EVA)  
 Frame: nylon  
 Temple: nylon  
 Temple tips: thermoplastic rubbers (TPR)  
 Screw: stainless steel  
 Nosepiece: thermoplastic rubbers (TPR)

### Part No.

### Lens Marking

### Frame Marking

CHB410DTP	P	P Z87 + / P c SEI CAN/CSA Z94.3-15
CHB418DTP	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15
CHB420DTP	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15
CHRT410DTP	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15
CHRT420DTP	P	P Z87 + S / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark

### Frame Marking Symbols

P: Manufacturer's mark  
 Z87: ANSI standard for eye and face protection devices  
 +: High impact  
 S: Special purpose  
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices



There's more to see at  
**PYRAMEXSAFETY.COM**

(P) 800.736.8673 | (F) 901.861.4967