



SGL106

## Crossover™ ANSI • CSA •



VENTED FRAME





INCLUDES STRAP

Removable indirect vented rolled rubber gasket // Adjustable detachable strap with quick release



### Black and Gray Frame | 3 Variations

-  SBG10610DT •• Clear **H2X** AF
-  SBG10620DT •• Gray **H2X** AF
-  SBG10680DT •• I/O Mirror AF

### Gray and Lime Frame | 1 Variation

-  SGL10610DT •• Clear **H2X** AF

Part No.	Lens Marking	Temple Marking
SBG10610DT	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10620DT	P Z87 + U6 L2.5	P Z87 + / P c SEI CAN/CSA Z94.3-15
SBG10680DT	P Z87 + U6 L1.7	P Z87 + / P c SEI CAN/CSA Z94.3-15
SGL10610DT	P Z87 + U6	P Z87 + / P c SEI CAN/CSA Z94.3-15

### Lens Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

### UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

### Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% max visible light

### Temple Marking Symbols

P: Manufacturer's mark

Z87: ANSI standard for eye and face protection devices

+: High impact

c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

### General Specifications

Weight: 32.9 gm

PD: 64 mm

Bridge: 13.6 mm

Lens base: 9 curve

Lens size diagonal: 78.6 mm

Lens size vertical: 46.8 mm

Lens thickness: 2.0 mm

Overall length (lens - tip): 170 mm

Overall width (hinge - hinge): 130.5 mm

Closest point between temple tips: 83 mm

Closest point between lens: 9.5 mm

Strap Length: 165 - 195 mm

### Materials

Lens: polycarbonate

Rubber gasket: polycarbonate & thermoplastic rubbers (TPR)

Temples: polycarbonate

Temple strap: polyester

Hook for temple strap: nylon

Takeup loop for strap: nylon