

DEFIANT®

FOR OVER PRESCRIPTION SPECTACLES

**PART**

SB1010S*

SB1010SJ**

LENS Clear Jumbo Size Clear*For use over prescription spectacles.*

- Tilt type adjustment allows optimum visibility.
- Lenses are coated for superior scratch resistance.
- Lenses provide 99.9% protection against harmful UV rays.
- Temples adjust to four settings.
- For use over prescription spectacles.

GENERAL SPECIFICATION

Bridge: 34.4mm

Lens Base: 2.25 Curve

Lens Size Diagonal: 157.8mm

Lens Size Vertical: 66mm

Lens Thickness: 2.20mm

Overall Length (Lens-Tip): 143-159mm

Overall Width (Hinge-Hinge): 160mm

PD: 68mm

Weight: 45gm

PACKAGING

Polybag: 1 pc



Inner Box: 12 pcs

Case: 300 pcs

DEFIANT®

FOR OVER PRESCRIPTION SPECTACLES

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	Wrap around design with side protection
Frame	N/A	N/A
Side Shields	Polycarbonate	Integral to lens
Nose Piece	Bridge-Polycarbonate	Integral to lens
Sleeve (on temple)	Nylon 6.6	Adjustable to 5 lengths
Temple	Nylon 6.6	Ratchet/tilt to multiple positions
Temple Tip	N/A	N/A
Hinge	Nylon 6.6	3 barrel type, integral to clip/sleeve
Screw	Brass	Standard hinge screw

PART	LENS	LENS MARKING	FRAME MARKING
SB1010S	 Clear	P Z87 + U6	P Z87 +
SB1010SJ	 Clear	P Z87 + U6	P Z87 +

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact