



ESDA1

## Ergo Advantage Electrostatic Dissipation (ESD) Tile

Following strict quality control of our manufacturing process each tile delivers consistent ESD performance:

- Surface Resistivity:  $3 \times 10^7$  Ohm
- Volume Resistivity:  $3 \times 10^7$  Ohm
- Test Procedure: ANSI/ESD S7.1

Custom resistivity performance within the dissipative range is also available. Minimum quantities apply.

- Durometer:** Shore Hardness "A" 35 (+/- 5)
- Dimensions:** 18" x 18" x 1" (2.25 sq.ft/tile)
- Weight:** 5.5 lbs
- Composition:** 100% Recycled PVC
- Warranty:** 20 Year Warranty Against Manufacturer's Defects
- Tear Strength:** 156 – 367 lbs/in
- Tensile Strength:** 1170 – 1620 psi

**Tile Type:**  
ESDA1

Have a unique color requirement?  
Please reach out and ask for  
more details.

## Take Advantage of the Benefits

Our ESD tile delivers all of the ergonomic benefits of our standard anti-fatigue product while providing industry leading ESD performance.

Through our proprietary manufacturing process, Ergo Advantage ESD tiles retain the required ESD performance through the full volume of the tile as compared to other mats that only offer "surface resistivity".

Aluminum or Copper Tape can be used as the grounding agent when installed over a non-grounded floor.

The advanced **Versatile Interlock System** allows for ease and efficiency during installation and future modifications.

Manufactured with **100% Recycled PVC** for waste reduction.