



# 12" Low Profile Flushmount

1000 lms | 120-277VAC | Model 54436241 | Part FM-12-14-840-MV-N-B

- > Energy Saving 14 Watt Integrated LED
- > Uses 81% Less Energy than Equivalent 75 Watt Incandescent Bulb
- > Cool White 4000k CCT
- > Lasts 45 years or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



## SPECIFICATIONS

Model	54436241
Part	FM-12-14-840-MV-N-B
Description	12" Round Low Profile - Non-Dimmable
Input Voltage (VAC)	120-277
Wattage	14
Average Rated Life <sup>1</sup>	50,000 hours
Typical Lumens <sup>2</sup>	1000
CCT <sup>3</sup>	4000k
Location Rating	UL Damp
CRI <sup>4</sup>	80
Beam Angle	120
Operating Temperature	Min -4°F (-20° C), Max 95°F (35° C)
Power Factor	>0.9
R9	14
DUV	0.00111
CBCP	245
Operating Frequency (Hz)	50/60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754

ETI

**LED lighting facts**  
A Program of the U.S. DOE

<b>Light Output (Lumens)</b>	<b>1000</b>
<b>Watts</b>	<b>14</b>
<b>Lumens per Watt (Efficacy)</b>	<b>71.43</b>

<b>Color Accuracy</b> Color Rendering Index (CRI)	<b>80</b>
--	-----------

**Light Color**  
Correlated Color Temperature (CCT) **4000 (Bright White)**

2700K    3000K    4500K    6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: YN84-A6QQ8D (1/21/2017)  
 Model Number: 544362###(##=41-50)  
 Type: Luminaire - Decorative





# 12" Low Profile Flushmount

1000 lms | 120-277VAC | Model 54436241 | Part FM-12-14-840-MV-N-B

## SHIPPING INFORMATION

Model	54436241
Part	FM-12-14-840-MV-N-B
UPC	849489001241
Product Dimensions (L x W x H in.)	11.5 x 11.5 x 2.95
Product Dimensions (L x W x H cm.)	29.2 x 29.2 x 7.5
Product Weight (lbs.)	1.08
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	6
Master Carton Bar Code	50849489001246
Master Carton Dimensions (L x W x H in.)	20.47 x 12.95 x 13.15
Master Carton Dimensions (L x W x H cm.)	52.0 x 32.9 x 33.4
Master Carton Weight (lbs)	11.35
Pallet Quantity	108

## AVAILABLE ACCESSORIES

Model	Description
95443620101	Diffuser Lens

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.etissl.com/fcc15b](http://www.etissl.com/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**ETi Solid State Lighting, Inc.**  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256