



# 4' High Lumen Output Vapor Tight

5400 lm | 120-277VAC | Model 54465141 | Part VT-4-51-840-MV

- > Energy Saving 51 Watt Integrated LED
- > Cool White 4000K CCT
- > Lasts 45 years\* or 50,000 Hours Continuous Use
- > Maintenance Free — No Bulb Replacements
- > 5 Year Limited Warranty



## SPECIFICATIONS

<b>Model</b>	54465141
<b>Part</b>	VT-4-51-840-MV
<b>Description</b>	4' Vapor Tight
<b>Input Voltage (VAC)</b>	120-277
<b>Wattage</b>	51
<b>Dimmability</b>	Non-dimmable
<b>Average Rated Life<sup>1</sup></b>	50,000 hours
<b>Typical Lumens<sup>2</sup></b>	5400
<b>CCT<sup>3</sup></b>	4000K
<b>Location Rating</b>	UL Wet (IP65 Rated)
<b>CRI<sup>4</sup></b>	≥80
<b>Beam Angle</b>	120°
<b>Operating Temperature</b>	Min -4°F (-20° C) Max 113°F (45° C)
<b>Power Factor</b>	>0.9
<b>R9</b>	20
<b>DUV</b>	-0.00149
<b>CBCP</b>	1500
<b>Operating Frequency (Hz)</b>	50/60

1 Hours lifetime with 70% lumen maintenance  
 2 Thermally stable typical lumens (±10%)  
 3 Thermally stable CCT (±10%)  
 4 Color rendering index/Ra

ETI

**LED lighting facts**  
A Program of the U.S. DOE

<b>Light Output (Lumens)</b>	<b>5400</b>
<b>Watts</b>	<b>51</b>
<b>Lumens per Watt (Efficacy)</b>	<b>105.88</b>
<b>Color Accuracy</b> Color Rendering Index (CRI)	
<b>80</b>	
<b>Light Color</b> Correlated Color Temperature (CCT)	
<b>4000 (Bright White)</b>	
Warm White	Bright White
2700K	3000K
4500K	6500K

All results are according to IESNA LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.

Visit [www.lightingfacts.com](http://www.lightingfacts.com) for the Label Reference Guide.

Registration Number: 5BAM-HC53F1 (11/2/2017)  
 Model Number: 544651##(##=41-50)  
 Type: Luminaire - Linear

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
 Call: 1.855.ETi.SSLI  
 1.855.384.7754





# 4' High Lumen Output Vapor Tight

5400 lms | 120-277VAC | Model 54465141 | Part VT-4-51-840-MV



## SHIPPING INFORMATION

Model	54465141
Part	VT-4-51-840-MV
UPC	849489009919
Product Dimensions (L x W x H in.)	48 x 4.6 x 3
Product Dimensions (L x W x H cm.)	122 x 11.7 x 7.6
Product Weight (lbs.)	4.12
Inner Carton Quantity	N/A
Inner Carton Bar Code	N/A
Inner Carton Dimensions (L x W x H in.)	N/A
Inner Carton Dimensions (L x W x H cm.)	N/A
Inner Carton Weight (lbs)	N/A
Master Carton Quantity	2
Master Carton Bar Code	50849489009914
Master Carton Dimensions (L x W x H in.)	50.91 x 7.32 x 5.35
Master Carton Dimensions (L x W x H cm.)	129.3 x 18.6 x 13.6
Master Carton Weight (lbs)	11.57
Pallet Quantity	110

## COMPATIBILITY

Dimmers: NA  
Sensors: 90600145

## AVAILABLE ACCESSORIES

Model	Part	Description	Wattage	Input Voltage	Case Pack
90600145	NA	ON/OFF motion sensor	NA	120-277	4

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see [www.ETiSSL.com/fcc15b](http://www.ETiSSL.com/fcc15b)

**TO ORDER:**  
[www.ETiSSL.com](http://www.ETiSSL.com)  
Call: 1.855.ETi.SSLI  
1.855.384.7754

**ETi Solid State Lighting, Inc.**  
720 Corporate Woods Parkway  
Vernon Hills, IL 60061  
Phone: 855.384.7754  
Fax: 847.383.6256