

- > Energy Saving 40 Watt Integrated LED
- > Cool White 4000k CCT
- > Lasts 45 years\* or 50,000 Hours **Continuous Use**
- > Maintenance Free No **Bulb Replacements**
- > 5 Year Limited Warranty

## 4' Vapor Tight with Battery Backup

3600 lms | 120-277VAC | Model 54656341 | Part VT-4-40-840-MV-EM



### **SPECIFICATIONS**

54656341 Model

VT-4-40-840-MV-EM Part

4' Vapor Tight with Battery Backup Description

120-277 Input Voltage (VAC)

40 Wattage

Non-dimmable Dimmability 50.000 hours Average Rated Life<sup>1</sup>

3600 Typical Lumens<sup>2</sup> 4000k CCT<sup>3</sup> **UL Wet Location Rating** ≥80 CRI<sup>4</sup> NA **Beam Angle** 

Min -13°F (-25° C), **Operating Temperature** 

Max 113°F (45° C)

>0.9 **Power Factor** 16 R9 0.0011 DUV 1043 **CBCP** Operating Frequency (Hz) 50/60

- 1 Hours lifetime with 70% lumen maintenance
- 2 Thermally stable typical lumens (±10%) 3 Thermally stable CCT (±10%)
- 4 Color rendering index/Ra











TO ORDER: www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754



# 4' Vapor Tight with Battery Backup

3600 lms | 120-277VAC | Model 54656341 | Part VT-4-40-840-MV-EM



#### SHIPPING INFORMATION

Model 54656341

Part VT-4-40-840-MV-EM
UPC 849489009926

Product Dimensions (L x W x H in.) 48 x 4.6 x 3

Product Dimensions (L x W x H cm.) 122 x 11.7 x 7.6

Product Weight (lbs.) 6.79
Inner Carton Quantity N/A
Inner Carton Bar Code N/A
Inner Carton Dimensions (L x W x H in.) N/A
Inner Carton Dimensions (L x W x H cm.) N/A
Inner Carton Weight (lbs) N/A
Master Carton Quantity 2

Master Carton Bar Code50849489009921Master Carton Dimensions (L x W x H in.)50.91 x 7.32 x 5.35Master Carton Dimensions (L x W x H cm.)129.3 x 18.6 x 13.6

Master Carton Weight (lbs) 14.87
Pallet Quantity 110

#### **COMPATIBILITY**

Dimmers: NA

Sensors: 90600145

## **AVAILABLE ACCESSORIES**

 Model
 Part
 Description
 Wattage
 Input
 Case

 90600145
 NA
 ON/OFF motion sensor
 NA
 120-277
 4

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation. For FCC Part 15 user information, Please see www.ETilSSL.com/fcc15b

TO ORDER: www.ETiSSL.com Call: 1.855.ETi.SSLI 1.855.384.7754 ETi Solid State Lighting, Inc. 720 Corporate Woods Parkway Vernon Hills, IL 60061 Phone: 855.384.7754 Fax: 847.383.6256