

Easley™

Built-in browguard

Adjustable nosepiece

Ventilated temples

Available in a Carhartt polybag



CHB810ST •• (polybag)
Clear Anti-fog Lens with Black and Tan Frame



CHB818ST •• (polybag)
Sandstone Bronze Anti-fog Lens with Black and Tan Frame



CHB820ST •• (polybag)
Gray Anti-fog Lens with Black and Tan Frame



Polybag



There's more to see at
PYRAMEXSAFETY.COM
(P) 800.736.8673 | (F) 901.861.4967

All safety eyewear meets ANSI Z87.1+ standards (•) and provides 99% protection from harmful UV rays. All lenses are hard coated polycarbonate scratch-resistant. Some options meet Canadian CSA Z94.3 (•) – SEI third-party certification. For specific lens options, visit our website or contact your sales representative.

Easley™

General Specifications

Weight: 31 gm
 Bridge: 11.8 mm
 Lens base: 9 curve
 Lens size diagonal: 62.1 mm
 Lens size vertical: 44.9 mm
 Lens thickness: 2.2 mm
 Overall length (lens - tip): 165.4 mm
 Overall width (hinge - hinge): 144.1 mm
 Closest point between temple tips: 93 mm
 Closest point between lens: 11.8 mm

Materials

Lens: polycarbonate (PC)
 Foam: thermoplastic rubber (TPR)
 Frame: polycarbonate (PC)
 Temple: polycarbonate (PC)
 Temple tips: thermoplastic rubber (TPR)
 Screw: stainless steel
 Nosepiece: polyvinyl chloride (PVC)

Part No.	Lens Marking	Frame Marking
CHB810ST	P +	P Z87 + / P c SEI CAN/CSA Z94.3-15
CHB818ST	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15
CHB820ST	P + S	P Z87 + / P c SEI CAN/CSA Z94.3-15

Lens Marking Symbols

P: Manufacturer's mark
 +: High impact
 S: Special purpose

Frame Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI CAN/CSA Z94.3-15: CAN/CSA standard for eye and face protection devices

