

EMERGE®

STYLISH DUAL FRAME WITH FULL EYE PROTECTION



Black Frame

| Part | Lens |
|--------------|-------------------------------------|
| SB7910DRX••• | <input type="checkbox"/> Clear |
| SB7910D15•• | <input type="checkbox"/> Clear +1.5 |
| SB7910D20•• | <input type="checkbox"/> Clear +2.0 |
| SB7950SF•• | <input type="checkbox"/> 5.0 IR |
| SB7960SF•• | <input type="checkbox"/> 3.0 IR |

Translucent Gray Frame

| Part | Lens |
|--------------|-------------------------------------|
| SG7910DRX••• | <input type="checkbox"/> Clear |
| SG7910D15••• | <input type="checkbox"/> Clear +1.5 |
| SG7910D20••• | <input type="checkbox"/> Clear +2.0 |

Translucent Caramel Frame

| Part | Lens |
|---------------|-------------------------------------|
| STC7910DRX••• | <input type="checkbox"/> Clear |
| STC7910D15••• | <input type="checkbox"/> Clear +1.5 |
| STC7910D20••• | <input type="checkbox"/> Clear +2.0 |

- Suitable for both working environments and sports activities.
- Soft nose piece provides comfort for extended use without slipping.
- Stylish dual lens with full eye protection, plano lens, prescription lens, and full reader lens adaptable.
- Will accommodate an Rx lens to the maximum of +3 to -3 diopters.

GENERAL SPECIFICATION

| |
|---|
| Bridge: 13mm |
| Closest Point Between Lens: 17.7mm |
| Closest Point Between Temple Tips: 83mm |
| Lens Base: 6 Curve |
| Lens Size Diagonal: 58mm |
| Lens Size Vertical: 42.5mm |
| Lens Thickness: 2.2mm |
| Overall Length (Lens-Tip): 163mm |
| Overall Width (Hinge-Hinge): 135mm |
| PD: 68mm |
| Weight: 30gm |

PACKAGING












Polybag: 1pc

Inner Box: 12 pcs

Case: 300 pcs

EMERGE®**STYLISH DUAL FRAME WITH FULL EYE PROTECTION**

| COMPONENT | MATERIAL | FEATURES |
|------------|-----------------|---|
| Lens | Polycarbonate | 6 base curve, dual lens frame style |
| Frame | G300 Nylon | Wrap around design with wide temples for extended side protection |
| Nose piece | PVC | Glued onto the nose bridge, pillow softness |
| Temple | Polycarbonate | Spatula Type |
| Hinge | Polycarbonate | 3 barrel type, integral to frame/temple |
| Screw | Stainless Steel | Standard hinge screw |

| PART | LENS | LENS MARKING | FRAME MARKING |
|------------|--|--------------|------------------------------------|
| SB7910DRX |  Clear | P + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-07 |
| SB7910D15 |  Clear +1.5 | P + U6 | P Z87 + 1.5 |
| SB7910D20 |  Clear +2.0 | P + U6 | P Z87 + 2.0 |
| SB7950SF |  5.0 IR | P + | P Z87 + / P c SEI CAN/CSA Z94.3-07 |
| SB7960SF |  3.0 IR | P + | P Z87 + / P c SEI CAN/CSA Z94.3-07 |
| SG7910DRX |  Clear | P + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-07 |
| SG7910D15 |  Clear +1.5 | P + U6 | P Z87 + 1.5 |
| SG7910D20 |  Clear +2.0 | P + U6 | P Z87 + 2.0 |
| STC7910DRX |  Clear | P + U6 | P Z87 + / P c SEI CAN/CSA Z94.3-07 |
| STC7910D15 |  Clear +1.5 | P + U6 | P Z87 + 1.5 |
| STC7910D20 |  Clear +2.0 | P + U6 | P Z87 + 2.0 |

LENS MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

W: Welding Filter

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING**Symbols:**

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

+1.5, 2.0: Rx

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices