





Glossy Black Frame

US

Part Lens

SB5110DT••• SB5120DT • • • •

Gray H2X Anti-Fog Shooter's Amber H2X Anti-Fog SB5133DT••

SB5155DT • • • Sky Red Mirror Anti-Fog SB5170DT • • • Silver Mirror Anti-Fog SB5175DT • • Blue Mirror Anti-Fog

SB5180DT• Indoor/Outdoor Mirror Anti-Fog

Clear H2X Anti-Fog SCG5165DT•

Ice Blue Mirror Anti-Fog

Part

Charcoal Gray Frame

Lens

• Sporty style with maximum protection.

- · Curved lens with side window gives fashionable look with panoramic view.
- Durable frame gives a pressure free fit.
- Soft nose piece and rubber insert temple tips provide a comfortable fit.
- Scratch resistant lenses filter out 99.9% of harmful UV rays.

GENERAL SPECIFICATION
Bridge: 13.4mm
Closest Point Between Lens: 14.8mm
Closest Point Between Temple Tips: 93mm
Lens Base: 8 Curve
Lens Size Diagonal: 70.8mm
Lens Size Vertical: 44mm
Lens Thickness: 2.30mm
Overall Length (Lens-Tip): 157mm
Overall Width (Hinge-Hinge): 127.5mm
PD: 68mm
Weight: 29gm



PACKAGING Polybag: 1pc Inner Box: 12 pcs Outer Carton: 300 pcs

COMPONENT	MATERIAL	FEATURES	
Lens	Polycarbonate	8 base curve, wrap around design with side protection	
Side Window Lens	Polycarbonate	Along with the front lens makes full wrap around image	
Frame	Nylon	Durable & flexible, sporty style	
Nose Piece	PVC	Universal	
Temple	Nylon	Spatula	
Temple Tip	PVC	Comfortable & good for color variants	
Hinge	Nylon	3 barrel type, integral to frame & temples	
Screw	Stainless Steel	Standard hinge screw	

PART	LENS	LENS MARKING	FRAME MARKING
SB5110DT	Clear H2X Anti-Fog	P Z87 + U6	P Z 8 7 +
SB5120DT	Gray H2X Anti-Fog	P Z87 + U6 L2.5	P Z 8 7 +
SB5133DT	Shooter's Amber H2X Anti-Fog	P Z87 + S	P Z 8 7 +
SB5155DT	Sky Red Mirror Anti-Fog	P Z87 + S	P Z 8 7 +
SB5170DT	Silver Mirror Anti-Fog	P Z87 + S	P Z 8 7 +
SB5175DT	Blue Mirror Anti-Fog	P Z87 + S	P Z 8 7 +
SB5180DT	Indoor/Outdoor Mirror Anti-Fog	P Z87 + S	P Z 8 7 +
SCG5165DT	Ice Blue Mirror Anti-Fog	P Z87 + S	P Z 8 7 +

LENS MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

- +: High Impact
- H: Small Head Size
- S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%

U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%

U3: Max Effective Far UV= .07% / Max Near UV= 1.4%

U4: Max Effective Far UV= .04% / Max Near UV= .5%

U5: Max Effective Far UV= .02% / Max Near UV= .2%

U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact