

**72706SB1**

6' DuraTech® Mini Class 1 Personal SRL-P with Steel Snap Hook, Includes Steel Dorsal Connecting Carabiner

**Features :**

- Features internal locking pawls and ViewPack® external energy absorber for even deceleration
- Long-wearing Dyneema® web lifeline resists abrasion while providing trusted strength.
- Nylon housing provides impact resistance in most worksite conditions
- Plated steel swivel-eye helps to prevent lifeline twisting and provide smooth operation
- Features alloy steel snap hook anchorage connector
- Includes alloy steel dorsal connecting carabiner
- May be anchored up to 5' below the dorsal D-ring with no edge hazards for user's weighing up to 310 lb max.
- Complies with ANSI Z359.14-2021 Class 1 SRL-P. [Learn more and download White Paper](#)



Material Specifications	
<b>Webbing</b>	Dyneema®/Polyester blend; 4,500 lb min.
<b>Energy Absorber</b>	Polyester tear-away
<b>Anchorage Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength
<b>Dorsal Connector</b>	Plated alloy steel; 5,000 lb min. static strength with 3,600 lb gate strength

Performance Specifications	
<b>Static Strength</b>	3,600 lb min.
<b>ANSI SRL Class/Type</b>	Class 1 SRL-P
<b>Avg. Arrest Force</b>	900 lb
<b>Max. Arrest Force</b>	1,800 lb
<b>Max. Arrest Distance</b>	42"
<b>ANSI User Capacity</b>	130 to 310 lb max.
<b>OSHA User Capacity</b>	130 to 310 lb max.

Compliant With:	
<b>OSHA</b>	1926.502 and 1910.66
<b>ANSI</b>	Z359.14-2021
<b>CSA</b>	Z259.2.2-2017

Sizes & Part Numbers		
72706SB1 (ANSI Compliant)	C72706SB1 (CSA Compliant)	