

# FASTRAC®

MAXIMUM SINGLE LENS PROTECTION



## PART

S1410S

S1420S

## LENS

Clear

Gray

- 100% polycarbonate frame/lens combination provides maximum single lens protection.
- Lenses are hard coated for superior scratch protection, provide 99.9% protection against harmful UV rays.

### GENERAL SPECIFICATION

Bridge: 16mm

Lens Base: 10 Curve

Lens Size Diagonal: 54/57.5mm

Lens Size Vertical: 43mm

Lens Thickness: 2.32mm

Overall Length (Lens-Tip): 113mm

Overall Width (Hinge-Hinge): 140mm

PD: 78mm

Weight: 24g

### PACKAGING

Polybag: 1pc



Inner Box: 12pcs

Case: 300pcs

# FASTRAC®

MAXIMUM SINGLE LENS PROTECTION

COMPONENT	MATERIAL	FEATURES
Lens	Polycarbonate	10 base curve, molded lens attached to the frame
Frame	Polycarbonate	N/A
Nose Piece	Polycarbonate	N/A
Temple	Polycarbonate	N/A

PART	LENS	LENS MARKING	FRAME MARKING
S1410S	 Clear	P Z87 + U6	P Z87 +
S1420S	 Gray	P Z87 + U6 L2.5	P Z87 +

## LENS MARKING

### Symbols:

P: Manufacturer's mark  
 Z87: ANSI standard for Eye and Face protection devices  
 +: High Impact  
 H: Small Head Size  
 S: Special Purpose

### UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7%  
 U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3%  
 U3: Max Effective Far UV= .07% / Max Near UV= 1.4%  
 U4: Max Effective Far UV= .04% / Max Near UV= .5%  
 U5: Max Effective Far UV= .02% / Max Near UV= .2%  
 U6: Max Effective Far UV= .01% / Max Near UV= .1%

### Visible Light Filters:

L1.3: 85% Max. Visible Light  
 L1.7: 55% Max. Visible Light  
 L2.5: 29% Max. Visible Light  
 L3: 18% Max. Visible Light

## FRAME MARKING

### Symbols:

P: Manufacturer's mark  
 Z87: ANSI standard for Eye and Face protection devices  
 +: High Impact