

Fyxate™ ANSI • CSA •



Dielectric // Rubber temple tips and nosepiece // Single wraparound lens // Flame resistant foam padding available on select options // Quick release strap available on foam padded options only



Black Temples | 5 Variations

- SB10210S •• Clear
- SB10210ST •• Clear **H2X AF**
- SB10220S •• Gray
- SB10220ST •• Gray **H2X AF**
- SB10280S •• I/O Mirror

Black Temples with Foam Padding | 3 Variations

- SB10210STMFP •• Clear **H2MAX AF**
- SB10220STMFP •• Gray **H2MAX AF**
- SB10225STMFP •• Light Gray **H2MAX AF**

Lime Temples with Foam Padding | 2 Variations

- SBL10210STMFP •• Clear **H2MAX AF**
- SBL10220STMFP •• Gray **H2MAX AF**



SB102



SB102 - FOAM

Part No.	Lens Marking	Temple Marking	General Specifications	Materials
SB10210S	P Z87 + U6	P Z87 + / P c SEI Z94.3	Weight: 23.2 gm 46.35 gm (with foam)	Lens: polycarbonate
SB10210ST	P Z87 + U6	P Z87 + / P c SEI Z94.3	Bridge: 12.8 mm	Nosepiece: thermoplastic rubber (TPR)
SB10220S	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	Lens base: 9.5 curve	Temples: polycarbonate & thermoplastic elastomers (TPE)
SB10220ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3	Lens size diagonal: 75.5 mm	Temple tips: polyvinyl chloride (PVC)
SB10280S	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3	Lens size vertical: 42.72 mm	Foam gasket: nylon and ethylene-vinyl acetate (EVA)
SB10210STMFP	P Z87 + U6 X	P Z87 + / P c SEI Z94.3	Lens thickness: 1.95 mm	Strap: polyester
SB10220STMFP	P Z87 + U6 L 2.5 X	P Z87 + / P c SEI Z94.3	Overall length (lens - tip): 160.8 mm	
SB10225STMFP	P Z87 + U6 L 2.5 X	P Z87 + / P c SEI Z94.3	Overall width (hinge - hinge): 129 mm	
SBL10210STMFP	P Z87 + U6 X	P Z87 + / P c SEI Z94.3	Closest point between temple tips: 73 mm	
SBL10220STMFP	P Z87 + U6 L 2.5 X	P Z87 + / P c SEI Z94.3		

Lens Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 S: Special Purpose
 X: Tested Anti-fog

UV Filter Transmittance

U6: .01% max effective far UV • .1% max near UV

Visible Light Filters

L1.7: 55% Max. Visible Light
 L2.5: 29% max visible light

Temple Marking Symbols

P: Manufacturer's mark
 Z87: ANSI standard for eye and face protection devices
 +: High impact
 c SEI Z94.3: CAN/CSA standard for eye and face protection devices