G304 | G304T | G304TN













Top Shelf Chemical Splash Goggle

Part Lens
G304••• Clear
G304T••• Clear H2X Anti-Fog
G304TN•• Clear H2X Anti-Fog with Neoprene Strap

- Body tinted to reduce glare.
- Special one-way vent allows air to enter while keeping liquids out.
- Top shelf chemical splash goggle features generously sized heavy duty body and lens.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

| GENERAL SPECIFICATION |
|------------------------------------|
| Bridge: 42mm |
| Lens Base: 4.25 curve |
| Lens Size Diagonal: 150mm |
| Lens Size Vertical: 76mm |
| Lens Thickness: 2.2mm |
| Overall Length (Lens-Tip): N/A |
| Overall Width (Hinge-Hinge): 180mm |
| PD: 68mm |
| Weight: 68gm |

| PACKAGING | |
|-------------------|--|
| Polybag: 1pc | |
| Inner Box: 12 pcs | |
| Case: 144 pcs | |

G304 | G304T | G304TN

| COMPONENT | MATERIAL | FEATURES |
|--------------|------------------------------------|----------------------------------|
| Lens | Polycarbonate | Lens inset in PVC frame |
| Frame | PVC | Polyvinyl chloride, flexible fit |
| Nose Piece | PVC | Integral to frame |
| 2 cap vents | LPDE | Also hold elastic band in place |
| Elastic Band | 60% polyester 40% rubber thread | N/A |

| PART | LENS | LENS MARKING | FRAME MARKING |
|--------|--------------------|--------------|--|
| G304 | Clear | P | P Z87 + / P c SEI CAN/CSA Z94.3-07 |
| G304T | Clear H2X Anti-Fog | P | P Z87 + D3 D4 / P c SEI CAN/CSA Z94.3-07 |
| G304TN | Clear H2X Anti-Fog | P | P Z 8 7 + |

LENS MARKING

Symbols:

P: Manufacturer's mark Z87: ANSI standard for Eye and Face protection devices

+: High Impact

H: Small Head Size

S: Special Purpose

UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7% U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3% U3: Max Effective Far UV= .07% / Max Near UV= 1.4% U4: Max Effective Far UV= .04% / Max Near UV= .5% U5: Max Effective Far UV= .02% / Max Near UV= .2% U6: Max Effective Far UV= .01% / Max Near UV= .1%

Visible Light Filters:

L1.3: 85% Max. Visible Light L1.7: 55% Max. Visible Light L2.5: 29% Max. Visible Light L3: 18% Max. Visible Light

FRAME MARKING

Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices

+: High Impact

D3: Droplet & Splash Test

D4: Dust Test

P c SEI CAN/CSA Z94.3-07: CAN/CSA for protection devices