





ANSI 287.1

Low Profile Chemical Splash Goggle Lens

Part G724T•

Gray Anti-Fog

- Low profile, modern sport design with anti-glare frame.
- · Direct ventilation prevents fogging.
- Adjustable elastic band and soft PVC frame.
- Scratch resistant polycarbonate lens provides 99% UVA/B/C protection.

# **GENERAL SPECIFICATION** Bridge: 21mm **Closest Point Between Lens: 18mm** Lens Base: 6 Curve Lens Size Diagonal: 82mm Lens Size Vertical: 52mm Lens Thickness: 2mm - 2.2mm Overall Width (Hinge-Hinge): 148mm PD: 64mm Weight: 35gm

PACKAGING
Polybag: 1pc
Inner Box: 12 pcs
Case: 144 pcs

COMPONENT	MATERIAL	FEATURES
Nose Piece	N/A	Integrated with PVC Frame
Frame	PVC	Low-profile frame design
Strap	N/A	Elastic Strap
Lens	Polycarbonate	6 base curve
Side Shields	N/A	Integrated with PVC Frame
Connector	Nylon	Thin and modern design

PART	LENS	LENS MARKING	FRAME MARKING
G724T	Gray Anti-Fog	P Z87 + U6 L3	P Z87 +

#### LENS MARKING

#### Symbols:

P: Manufacturer's mark

Z87: ANSI standard for Eye and Face protection devices +: High Impact H: Small Head Size S: Special Purpose

### UV Filter Transmittance:

U2: Max Effective Far UV= .1% / Max Near UV= 3.7% U2.5: Max Effective Far UV= .1% / Max Near UV= 2.3% U3: Max Effective Far UV= .07% / Max Near UV= 1.4% U4: Max Effective Far UV= .04% / Max Near UV= .5% U5: Max Effective Far UV= .02% / Max Near UV= .2% U6: Max Effective Far UV= .01% / Max Near UV= .1%

#### Visible Light Filters:

L1.3: 85% Max. Visible Light L1.7: 55% Max. Visible Light L2.5: 29% Max. Visible Light L3: 18% Max. Visible Light

## FRAME MARKING

Symbols:

P: Manufacturer's mark Z87: ANSI standard for Eye and Face protection devices +: High Impact