

GL406

POLYURETHANE



PU



Abrasion



Tear



Puncture

ANSI/ISEA 105 – CUT A1 | ABRASION 3 | PUNCTURE 2
EN388 – 3131X

Polyurethane Palm Coating // 13 Gauge Polyester
Liner // Touch Sensitivity // Low Particulate Shed //
Dark Color Hides Stains

GL406 S – 2XL

Suggested Applications

Electronics // General Duty // Parts Assembly //
Quality Control // Inspection // Construction

Glove Breakdown

Coating: Polyurethane
Liner: Polyester
Cuff: Polyester + Latex

⚠ WARNING: Cancer and Reproductive Harm –P65Warnings.ca.gov
This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

Testing Performance

ANSI/ISEA 105



EN388



ANSI/ISEA 105

Cut	1	2	3	4	5	6	7	8	9	X
Abrasion	1	2	3	4	5	6				
Puncture	1	2	3	4	5					

EN388

Abrasion	1	2	3	4				
Circular Blade Cut	1	2	3	4	5	X		
Tear	1	2	3	4				
Puncture	1	2	3	4				
Cut TDM-100	A	B	C	D	E	F	X	
Impact Rated	P	F	X					

Product markings may vary // Updated as of 01.23



Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11
------------	-------------	------------	---------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

Polybag: 12 pair
Case: 120 pair
Made in China