

Nitrile Dipped Glove Product Sheet









GL605

Polyester | Nitrile | Sandy + Smooth

EN388: 2016 - 4131X

Nitrile smooth full dipped coating // Double dipped nitrile sandy palm coating // 15 gauge polyester liner // Waterproof // Good grip in all conditions // Extra absorption

GL605 S - 2XL

Suggested Applications

Assembly Line // Manufacturer // HVAC // Aerospace // Handling Oily Parts // Utilities // Fisheries // Construction

Glove Breakdown

Type: Dipped Glove
Material: Nitrile Sandy + Smooth
Liner: 15 Gauge Polyester
Cuff: Polyester + Latex Elastic

This product contains components that may be a potential risk to allergic reactions (latex in the wrist cuff). Do not use in the event of hypersensitivity signs or a known allergy to latex.

glove size.

Small	Medium	Large	X-Large	2X-Large
7	8	9	10	11

All sizes comply with EN 420:2003 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Glove Sizing

The color of the binding around the cuff indicates the

Packaging

Pack: 12 pair	
Case: 120 pair	
Country of Origin: Chi	ina

Testing Performance EN388: 2016 - 4131X

Abrasion	1	2	3	4				
Circular Blade Cut	1	2	3	4	5	Χ		
Tear	1	2		4				
Puncture	1	2	3	4				
Cut TDM-100	Α	В	С	D	Ε	F		
Impact Rated	Р	F	Х					