

GL806HT

HIGH PERFORMANCE



ANSI/ISEA 105 – CUT A2 | ABRASION 4 | PUNCTURE 4
ANSI/ISEA 138 – IMPACT 2
EN388 – 2143XP

PVC Palm For Enhanced Grip // Level 2 Impact Protection // Slip-On Neoprene Cuff // Pull Tab for Easy On/Off // Mesh Stretch Fabric Back for Comfort and Breathability // Hi-vis Back for Enhanced Visibility // Hangtag for Retail Display

GL806HT S – 3XL

Suggested Applications

Rigging // Oil & Gas Drilling // Extraction & Refining // Fracking // Mining // Demolition // Construction // Handling Heavy Materials // Maintenance // Repair Operating Heavy Duty Machinery

Glove Breakdown

Palm: Polyvinyl Chloride
Liner: Polyester + Cotton
Back: Nylon + Spandex
Impact: Thermoplastic Rubber
Cuff: Neoprene

⚠ WARNING: Cancer and Reproductive Harm – P65Warnings.ca.gov

Testing Performance



ANSI/ISEA 105

Cut	1	2	3	4	5	6	7	8	9	X
Abrasion	1	2	3	4	5	6				
Puncture	1	2	3	4	5					

ANSI/ISEA 138

Impact	1	2	3
--------	---	---	---

EN388

Abrasion	1	2	3	4				
Circular Blade Cut	1	2	3	4	5	X		
Tear	1	2	3	4				
Puncture	1	2	3	4				
Cut TDM-100	A	B	C	D	E	F	X	
Impact Rated	P	F	X					

Product markings may vary // Updated as of 11.22



Glove Sizing

Small 7	Medium 8	Large 9	X-Large 10	2X-Large 11	3X-Large 12
------------	-------------	------------	---------------	----------------	----------------

All sizes comply with EN ISO 21420 for comfort, fit and dexterity. Only wear the correct size for your hand. Gloves that are too loose or too tight will restrict movement and will not provide the optimal level of protection.

Packaging

Inner Polybag: 1 pair on hangtag
Outer Polybag: 6 pair
Case: 60 pair
Made in Indonesia

