



## Product Data Sheet

### SPYDER Water Activated Gum Tape

#### Product Description:

SPYDER Industrial Grade Water-activated reinforced kraft paper tape is mainly used to replace pressure sensitive adhesive tape usually used for carton sealing. Used for two strip sealing cartons top and bottom. Works well on recycled cartons, and non-unitized loads. Recommended for use on light weight to average cartons up to 31 pounds (14 kg).



#### Item ID Numbers Here:

GTIS70KSR-WT,  
GTIS70KSR-WT3

#### Storage information:

It's recommended to store in clean and dry place. Damaged packaging shall be prevented. Not stored with volatile solvent. The temperature of storage shall be 39°F to 78° F and the humidity shall be between 40% and 50%. Rotate inventory recommended.

#### Wrap-Tite, Inc.

6200 Cochran Rd.  
Solon, Ohio 44139

Toll Free: 888-WRAP-TITE

Fax: 440-349-5432

www.wraptite.com - info@wraptite.com

Backing:	TOP	25 lb 42 g/m <sup>2</sup> Kraft Paper
	BOTTOM	25 lb 42 g/m <sup>2</sup> Kraft Paper
Reinforcement	MD	72mm 75 (1-1-1-1-1) Fiberglass
	CD	28mm 150 (1-1-1) Fiberglass Rhombus Pattern
Tensile Strength:	MD	51.7 lbs/in (ASTM D-3759)
	CD	18.01 lbs/in (ASTM D-3759)
Water-Activated Adhesive:		Starch Adhesive
Color:		Kraft
Total Thickness:		5.1 mil
Country of Origin		PRC

We believe the statements and information contained herein are accurate but are to be used only as general guidelines and are not warrants or guarantees because of the variety of possible uses. THERE IS NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THE BUYER MUST TEST THE SUITABILITY FOR EACH INTENDED APPLICATION BEFORE USING. WRAPTITE WILL NOT BE LIABLE FOR DAMAGES IN EXCESS OF THE PURCHASE PRICE OF ITS PRODUCTS OR FOR INCIDENTAL OR CONSEQUENTIAL DAMAGES.