



Bullhead Safety® HEARING PROTECTION

Corded Polyurethane Foam Earplugs

DESCRIPTION

These single-use foam earplugs provide simple, effective protection against hearing damage by greatly reducing environmental noise. Highly visible orange and shaped to conform to the ear canal, the soft, slow-recovery foam is rated for a protection level of NRR 33 dB.

INDUSTRY

- | | |
|---------------|--------------------------|
| Airport Crews | Utility/Waste Management |
| Construction | Transportation |
| Automotive | |
| Printing | |



FEATURES

- Single-use disposable earplugs
- 100% PVC-free polyurethane foam
- Extra-soft, lightweight foam seals the ear canal without pressure
- Bullet shaped provides a snug fit while gently conforming to the ear canal
- Expandable, slow rebound foam provides the best combination of comfort and protection for most users
- Made of soft non-allergenic material
- Each pair is individually poly bagged

ITEM **HP-F2**

NRR **33 DB**



SPECIFICATIONS

MATERIAL	SHAPE	COLOR	CORDED	METAL DETECTABLE	PAIRS PER BOX	ANSI S3.19-1974 NRR RATING	EN 352-2: 2002 SNR RATING
POLYURATHANE	BULLET	HV ORANGE	YES	NO	200	33 DB	36 DB

ANSI S3.19-1974 SOUND ATTENUATION DATA:

FREQUENCY (HZ)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
MEAN ATTENUATION (DB)	33.4	36.2	44.6	41.6	39.8	45.6	46.1	49.1	46.7	33 DB
STANDARD DEVIATION (DB)	4.7	4.3	3.6	3.6	2.7	4.2	4.5	4.7	4.9	

EN 352-2: 2002 SOUND ATTENUATION DATA:

FREQUENCY (HZ)	63	125	250	500	1000	2000	4000	8000
SOUND ATTENUATION (DB)	27.2	30.2	37	42.3	41.7	37.2	47.8	46.1
STANDARD DEVIATION (DB)	6.1	6.7	4.9	7.1	7.1	5.8	6.3	5.9
ASSUMED PROTECTION (DB)	21.1	23.5	32.1	35.2	34.6	31.4	41.5	40.2
	SNR = 36 DB H = 34 DB M = 34 DB L = 31 DB							

PACKAGING

	QUANTITY	HP-F2
EACH PAIR UPC	1	810292029517
INNER BOX GTIN	200 PAIRS/PACK	10810292029514
CASE GTIN	10 PK/CASE	20810292029511
CASE WEIGHT (IN POUNDS)		12

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
sales@BullheadSafety.com

BullheadSafety.com

