



Bullhead Safety® HEARING PROTECTION

Premium High-Visibility Foldable Earmuffs

DESCRIPTION

The HP-M2 is a foldable earmuff with high level attenuation. Conveniently folds away for easy storage. Over-the-head banded design provides maximum versatility for use with other PPE. Features ABS cups for their durability and impact resistance. The soft PVC cushions allows comfort in extended wearing conditions. NRR 23 dB.



INDUSTRY

| | |
|----------------------|--------------------|
| Assembly | Sanding |
| Cleaning | Welding |
| Demolition | Construction |
| Electrical | Machine Operations |
| Facility Maintenance | Painting |
| Grinding | Transportation |

ITEM **HP-M2**

NRR **23 dB**

FEATURES

- Adjustable and flexible reinforced plastic headband with 4-point suspension offers a custom fit
- Lightweight earmuff for extended wearability
- ABS (Acrylonitrile Butadiene Styrene) cups provide impact resistance
- Soft PVC ear cushions deliver long-wearing comfort
- Stainless steel wires prevent rust and corrosion

NRR
23 dB

SPECIFICATIONS

| MATERIAL | SHAPE | COLOR | ADJUSTABLE | ANSI S3.19-1974 NRR RATING | EN 352-2: 2002 SNR RATING |
|----------|----------|---------------------------|------------|----------------------------|---------------------------|
| ABS | SOFT PVC | HV YELLOW/GREEN AND BLACK | YES | 23 dB | - |

ANSI S3.19-1974 SOUND ATTENUATION DATA:

| FREQUENCY (Hz) | 125 | 250 | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 | NRR |
|-------------------------|------|------|------|------|------|------|------|------|------|-------|
| MEAN ATTENUATION (dB) | 16.2 | 17.8 | 28.7 | 33 | 34.1 | 38.6 | 38.5 | 38.7 | 37.9 | 23 dB |
| STANDARD DEVIATION (dB) | 3.8 | 1.8 | 2.5 | 2.9 | 2.8 | 2.3 | 2.8 | 3.5 | 4.1 | |

Headband Force = 2.7 lbs

EN 352-2: 2002 SOUND ATTENUATION DATA:

| FREQUENCY (Hz) | 63 | 125 | 250 | 500 | 1000 | 2000 | 4000 | 8000 |
|-------------------------|------|------|------|------|------|------|------|------|
| SOUND ATTENUATION (dB) | 18.8 | 15.4 | 17.9 | 27.8 | 36.3 | 35.4 | 42.4 | 39.5 |
| STANDARD DEVIATION (dB) | 4.1 | 4.1 | 3.5 | 2.7 | 3.7 | 3.6 | 2.6 | 5.4 |
| ASSUMED PROTECTION (dB) | 14.7 | 11.3 | 14.4 | 25.1 | 32.6 | 31.8 | 39.8 | 34.1 |

SNR = 28 dB H = 34 dB M = 26 dB L = 17 dB

PACKAGING

| | QUANTITY | ITEM ID |
|-------------------------|-------------|----------------|
| EACH PAIR | 1/BOX | 810292029647 |
| INNER PACK | - | NA |
| CASE | 20 BOX/CASE | 10810292029644 |
| CASE WEIGHT (IN POUNDS) | | 14.65 |

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
sales@BullheadSafety.com

BullheadSafety.com

