



Bullhead Safety® HEARING PROTECTION

Uncorded Reusable Silicone Earplugs

DESCRIPTION

These triple-flange silicone earplugs provide effective protection against hearing damage by greatly reducing environmental noise. High-visibility yellow and shaped to gently conform to the ear canal, the extra soft silicone is rated for a protection level of NRR 23 dB.

INDUSTRY

- | | |
|---------------|--------------------------|
| Airport Crews | Utility/Waste Management |
| Construction | Transportation |
| Automotive | |
| Printing | |




FEATURES

- Reusable earplugs
- Extra-soft, lightweight silicone seals the ear canal without pressure
- Manufactured through vulcanization, not mold injected for ultimate flexibility
- Environmentally friendly, 100% silicone
- Packaged 1 pair per personal carrying case (includes chain attachment)
- Triple-flange shape with firm handle provides an easy to insert, snug fit while gently conforming to the ear canal

ITEM **HP-S1**

NRR **23 dB**



SPECIFICATIONS

MATERIAL	SHAPE	COLOR	CORDED	METAL DETECTABLE	PAIRS PER BOX	ANSI S3.19-1974 NRR RATING	EN 352-2: 2002 SNR RATING
SILICONE	TRIPLE-FLANGE	HV YELLOW	NO	NO	200 PAIRS	23 dB	28 dB

ANSI S3.19-1974 SOUND ATTENUATION DATA:

FREQUENCY (Hz)	125	250	500	1000	2000	3150	4000	6300	8000	NRR
MEAN ATTENUATION (dB)	28.7	25.9	31.3	27.3	35.1	39.4	40.3	46.2	46.2	23 dB
STANDARD DEVIATION (dB)	5.5	4.5	4.5	2.8	4.3	4.2	5.6	6.1	3.7	

EN 352-2: 2002 SOUND ATTENUATION DATA:

FREQUENCY (Hz)	125	250	500	1000	2000	4000	8000
SOUND ATTENUATION (dB)	29.6	28.3	30.1	28.8	34.6	38.9	44
STANDARD DEVIATION (dB)	5.6	6	7.8	6	3.9	5.6	5.6
ASSUMED PROTECTION (dB)	24	22.3	22.3	22.8	30.7	33.3	38.4
	SNR = 28 dB	H = 30 dB	M = 24 dB	L = 23 dB			

PACKAGING

	QUANTITY	ITEM ID
EACH PAIR	1	810292029609
INNER BOX	100PAIRS/PACK	10810292029606
CASE	10 PK/CASE	20810292029603
CASE WEIGHT (IN POUNDS)		29

13915 Radium St NW
Ramsey, MN 55303

763-450-0110
sales@BullheadSafety.com

BullheadSafety.com

